



**Electronic Signatures and Infrastructures (ESI);
Testing Conformance and Interoperability of
Registered Electronic Mail Services;
Part 2: Test suites for interoperability testing of
providers using same format and transport protocols**

Reference

RTS/ESI-0019534-2v121

Keywords

interoperability, registered electronic mail, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	7
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Technical approach.....	8
4.1 Components of test cases and their identifiers	8
4.2 Adding new test cases to the test suite	9
5 Scenarios	10
5.1 Introduction	10
5.2 Abbreviations used in tables defining scenarios.....	11
5.3 Black-box model scenarios.....	12
5.3.1 Introduction.....	12
5.3.2 Scenarios for Store and Forward style	12
5.3.3 Scenarios for Store and Notify style	27
5.4 Scenarios for 4-corner model	31
5.4.1 Introduction.....	31
5.4.2 Scenarios for Store&Forward to Store&Forward	31
5.4.3 Scenarios for Store&Forward to Store&Notify	39
5.4.4 Scenarios for Store&Notify to Store&Forward	48
5.5 Scenarios for extended model	60
5.5.1 Introduction.....	60
5.5.2 Scenarios for S&F->S&F->S&F	60
5.5.3 Scenarios for S&F -> S&N -> S&F.....	69
6 REM Messages instances	79
6.1 Introduction and technical approach.....	79
6.2 Combinations of fields for headers in REM envelopes	80
6.2.1 Introduction.....	80
6.2.2 Combinations of fields for the REMS relay metadata MIME Header.....	80
6.2.3 Combinations of fields for the signed data MIME header	86
6.2.4 Combinations of fields for the REMS introduction section.....	86
6.2.4.1 Introduction	86
6.2.4.2 Combinations of fields for the REMS introduction MIME header	86
6.2.4.3 Combinations of fields for the multipart/alternative free text subsection header.....	86
6.2.4.4 Combinations of fields for the multipart/alternative html subsection header.....	87
6.2.5 Combinations of fields for the original message MIME section header.....	87
6.2.6 Combinations of fields for one REMS extension MIME section header.....	87
6.2.7 Combinations of fields for one ERDS evidence MIME section header.....	88
6.2.7.1 Combinations of fields for one XML ERDS evidence MIME section header	88
6.2.7.2 Combinations of fields for one PDF ERDS evidence MIME section header.....	89
6.2.8 Combinations of fields for the REMS signature MIME section header	90
6.3 Instances of REM payload.....	91
6.4 Instances of REMS notification.....	97
6.5 Instances of REMS receipts.....	101
6.6 Instances of REM dispatch.....	102
7 Other named sets	106
7.1 Named sets of participating REMSs.....	106
7.2 Named sets of additional requirements	106
7.3 Named sets of entities in receiving side	106

8	Test cases definition	107
8.1	Introduction	107
8.2	Test cases for black-box model	108
8.2.1	Test cases for Store&Forward style of operation.....	108
8.2.1.1	Introduction.....	108
8.2.1.2	Test cases for scenario REM_SF#1	109
8.2.1.3	Test cases for scenario REM_SF#2	109
8.2.1.4	Test cases for scenario REM_SF#3	110
8.2.1.5	Test cases for scenario REM_SF#4	110
8.2.1.6	Test cases for scenario REM_SF#5	110
8.2.1.7	Test cases for scenario REM_SF#6	111
8.2.1.8	Test cases for scenario REM_SF#7	111
8.2.1.9	Test cases for scenario REM_SF#8	112
8.2.1.10	Test cases for scenario REM_SF#9	112
8.2.1.11	Test cases for scenario REM_SF#10	113
8.2.1.12	Test cases for scenario REM_SF#11	113
8.2.1.13	Test cases for scenario REM_SF#12	114
8.2.1.14	Test cases for scenario REM_SF#13	114
8.2.2	Test cases for Store&Notify style of operation.....	115
8.2.2.1	Rules for REM messages	115
8.2.2.2	Rules for failure reasons.....	115
8.3	Test cases for 4-corner model.....	115
8.3.1	Introduction and general rules	115
8.3.2	Test cases for Store&Forward to Store&Forward scenarios.....	116
8.3.2.1	Rules for REM messages	116
8.3.2.2	Rules for failure reasons.....	116
8.3.3	Test cases for Store&Forward to Store&Notify scenarios.....	117
8.3.3.1	Rules for REM messages	117
8.3.3.2	Rules for failure reasons.....	117
8.3.4	Test cases for Store&Notify to Store&Forward scenarios.....	117
8.3.4.1	Rules for REM messages	117
8.3.4.2	Rules for failure reasons.....	117
8.4	Test cases for extended model.....	118
8.4.1	Test cases for scenarios S&F->S&F->S&F.....	118
8.4.1.1	Rules for REM messages	118
8.4.1.2	Rules for failure reasons.....	118
8.4.2	Test cases for scenarios S&F->S&N->S&F	118
8.4.2.1	Rules for REM messages	118
8.4.2.2	Rules for failure reasons.....	118
9	Test suite for REM Baseline	118
9.1	Introduction	118
9.2	Test cases for REM Baseline.....	119
9.2.1	Combinations of fields for the REM relay metadata header.....	119
9.2.2	Combinations of fields for the signed data MIME section header.....	119
9.2.3	Combinations of fields for the introduction MIME section header	119
9.2.4	Combinations of fields for the free text MIME subsection header	119
9.2.5	Combinations of fields for the HTML MIME subsection header.....	120
9.2.6	Combinations of fields for the original message MIME section header	120
9.2.7	Combinations of fields for the ERDS evidence MIME section header	120
9.2.8	Combinations of fields for the REMS signature MIME section header	120
9.2.9	Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#3	121
9.2.10	Test cases for REM Baseline built on scenario Scenario id: SREMS_SF_RREMS_SF#2	122
9.2.11	Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#6	123
9.2.12	Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#1	125
9.2.13	Test case for REM Baseline built on scenario SREMS_SF_RREMS_SF#7	125
Annex A (informative): Change History		127
History		128

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electronic Signatures and Infrastructures (ESI).

The present document is part 2 of a multi-part deliverable. Full details of the entire series can be found in part 1 [i.1].

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document defines:

- 1) A test suite for supporting interoperability tests within the field of Registered Electronic Mail (REM hereinafter) as specified in ETSI EN 319 532 parts 1 [3], 2 [4], 3 [5] and 4 [6]. The test suite defines test cases for the following environments:
 - Environments that correspond to the basic model as defined in ETSI EN 319 532-1 [3] where sender and all the entities at receiving side are subscribed to the same REMS. Test cases are defined for REMSs operating Store&Forward and for REMSs operating Store&Notify styles.
 - Environments that correspond to the 4-corner model as defined in ETSI EN 319 532-1 [3] where sender is subscribed to one REMS and the entities at receiving side are subscribed to another one, and no intermediate REMS is required for relaying REM messages between them. Test cases are defined for covering the three possible different combinations of styles, namely Store&Forward to Store&Forward, Store&Forward to Store&Notify, and Store&Notify to Store&Forward.
 - Environments that correspond to the extended model as defined in ETSI EN 319 532-1 [3] where sender is subscribed to one REMS and the entities at receiving side are subscribed to another one, and intermediate REMSs are required for relaying REM messages between them. Test cases are defined for covering two different combinations of styles, namely Store&Forward to Store&Forward to Store&Forward, Store&Forward to Store&Notify to Store&Forward.
- 2) A mechanism for documenting new test cases and expanding the aforementioned test suite.

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI EN 319 522-1](#): "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 1: Framework and Architecture".
- [2] [ETSI EN 319 522-2](#): "Electronic Signatures and Infrastructures (ESI); Electronic Registered Delivery Services; Part 2: Semantic contents".
- [3] [ETSI EN 319 532-1](#): "Electronic Signatures and Infrastructures (ESI); Registered Electronic Mail (REM) Services; Part 1: Framework and Architecture".
- [4] [ETSI EN 319 532-2](#): "Electronic Signatures and Infrastructures (ESI); Registered Electronic Mail (REM) Services; Part 2: Semantic Contents".
- [5] [ETSI EN 319 532-3](#): "Electronic Signatures and Infrastructures (ESI); Registered Electronic Mail (REM) Services; Part 3: Formats".
- [6] [ETSI EN 319 532-4](#): "Electronic Signatures and Infrastructures (ESI); Registered Electronic Mail (REM) Services; Part 4: Interoperability profiles".
- [7] [IETF RFC 8118](#): "The application/pdf Media Type".

- [8] [IETF RFC 2046](#): "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types".
- [9] [IETF RFC 2183](#): "Communicating Presentation Information in Internet Messages: The Content-Disposition Header Field".
- [10] [IETF RFC 5751](#): "Secure/Multipurpose Internet Mail Extensions (S/MIME) Version 3.2 Message Specification".
- [11] [IETF RFC 5322](#): "Internet Message Format".
- [12] [IETF RFC 2854](#): "The 'text/html' Media Type".
- [13] [IETF RFC 7303](#): "XML Media Types".
- [14] [IETF RFC 2045](#): "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] [ETSI TS 119 534-1](#): "Electronic Signatures and Infrastructures (ESI); Testing Conformance and Interoperability of Registered Electronic Mail Services; Part 1: Testing conformance".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the terms given in ETSI EN 319 532-1 [3] apply.

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ACC_REJ_EXP	ACCEptanceREJectionEXPIry
CONS_ACC	CONSignmentACCEptance
CONS_NOT	CONSignmentNOTification
CONS_NOT_FAIL	CONSignmentNOTificationFAILure
CONS_REJ	CONSignmentREJection
CONT_CONS	CONTentCONSignment
CONT_CONS_FAIL	CONTentCONSignmentFAILure
CONT_HAND	CONTentHANDover
CONT_HAND_FAIL	CONTentHANDoverFAILure
ERDS	Electronic Registered Delivery
EV_SET	Evidence SET
IREMS	Intermediate Registered Electronic Mail Service

NOT_F_ACC	NOTificationForACceptance
NOT_F_ACC_FAIL	NOTificationForACceptanceFAILure
REC_F_NERDS	RECeivedFromNonERDS
REL_ACC	RELayACceptance
REL_FAIL	RELayFAILure
REL_REJ	RELayREJection
REL_T_NERDS	RELayToNonERDS
REL_T_NERDS_FAIL	RELayToNonERDSFAILure
REM	Registered Electronic Mail
REMS	Registered Electronic Mail Service
RREM	Recipient's Registered Electronic Mail
RREMS	Recipient's Registered Electronic Mail Service
S&F	Store and Forward
S&N	Store and Notify
S/MIME	Secure/Multipurpose Internet Mail Extensions
SCN_ID	Scenario Identifier
SMIME	Secure/Multipurpose Internet Mail Extensions
SREM	Sender's Registered Electronic Mail
SREMS	Sender's Registered Electronic Mail Service
SUB_ACC	SUBmissionACceptance
SUB_REJ	SUBmissionREJection

4 Technical approach

4.1 Components of test cases and their identifiers

As it has been mentioned before the present document defines:

- 1) A test suite for supporting interoperability tests within the field of Registered Electronic Mail (REM hereinafter) as specified in ETSI EN 319 532 parts 1 [3], 2 [4], 3 [5] and 4 [6].
- 2) A mechanism for documenting new test cases and expanding the aforementioned test suite.

The present document follows a layered approach for building the definition of the test cases in the test suite, which can be summarized as follows:

- 1) Clause 5 defines a number of parameterized scenarios. A scenario consists of a number of entities, namely: sender, one or more REMSs, and the entities at receiving side - one or more recipients and/or one or more recipients' delegates -, which exchange different REM messages with time. Each scenario corresponds to one of the three models presented in ETSI EN 319 532-1 [3]. This clause presents a template for defining one scenario, in a way that resembles to some templates used for defining use cases scenarios in software engineering:

This template:

- Includes the enumeration of all the REM messages exchanged by the participating entities. This list of exchanged REM messages is one of the parameters of the scenario.
- Also includes a list of ERDS evidence sets, which, in the scenario, are incorporated in some REM messages.

One scenario may be used for defining several test cases depending on:

- The specific components of each exchanged REM message (suppressing or adding an optional header, or changing the value of a certain header field results in a different REM message and consequently a different test case).
- The entities at receiving part (for instance, changing one recipient by one recipient's delegate, or two recipients and one recipient's delegate results in a different the test case).

- A named set of additional requirements (for instance whether the original message contains or not attachments, is signed, is encrypted, etc.).
- In negative test cases, i.e. test cases where the service failed in consigning or handing over the message to one or more recipients, the reason(s) causing that failure.

This means that one test case corresponds to one scenario where all the exchanged REM messages have been completely defined in terms of their components, all the participating entities have been established, and all the additional requirements have also been defined. Taking the functional notation this can be expressed as follows:

TestCase#i = Scenario_id(<Receiving side identifier>, <REM message identifier 1>, <REM message identifier 2>, ..., <REM message identifier N>, <additional requirements set identifier>, <failure reasons>?)

Where:

- <Receiving side identifier> is the identifier assigned to a certain set of entities at receiving side;
 - <REM message identifier I> is the identifier of a specific instantiation of the aforementioned REM message, namely: REM payload, REM notification, REM Receipt, or REM dispatch, which are defined in clauses 6.3, 6.4, 6.5 and 6.6 respectively.
 - <additional requirements set identifier> is the identifier of a named set of additional requirements. Clause 7.2 defines a number of these named sets.
 - <failure reason(s)>? is the reason(s) that caused that the service failed in consigning or handing over the message to the recipient(s). It shall only appear in negative test cases.
- 2) Clauses 6.3, 6.4, 6.5 and 6.6 define specific instantiations of REM payloads, REM notifications, REM receipts and REM dispatches respectively. Each type of REM message is composed by several MIME sections, with their headers and bodies. One specific instantiation of a certain type of REM message is composed by one specific combination of MIME sections. Each MIME section in turn is formed by one certain combination of headers and has a specific value in its body. The present document defines a number of combinations of MIME sections in clauses 6.2.2, 6.2.3, 6.2.4.3, 6.2.4.4, 6.2.5, 6.2.6, 6.2.7 and 6.2.8, and assigns to each one a unique identifier. This allows to use again the functional notation, and define one instantiation of a certain type of REM message as follows:

REM message instance = Sequence(<outer most MIME header identifier>, <signed data MIME header section identifier>, <multipart/alternative free text MIME section identifier>, <multipart/alternative html MIME section>, <original message MIME section identifier>?, <extension MIME section identifier>*, <ERDS evidence MIME section identifier>*, <signature MIME section identifier>)

Where ? indicates a cardinality 0 or 1 for the affected MIME section, and * indicates a cardinality of 0 or more for the affected MIME sections.

- 3) Clauses 6.2.2, 6.2.3, 6.2.4.3, 6.2.4.4, 6.2.5, 6.2.6, 6.2.7 and 6.2.8 define specific instances for the REMS relay metadata MIME Header, the signed data MIME header, the multipart/alternative free text MIME section, the multipart/alternative html MIME section, original message MIME section, the extension MIME section, the ERDS evidence MIME section, and the signature MIME section respectively. Each clause defines different instances of the aforementioned headers and sections and assigns them unique identifiers that are used for defining specific instances of the different REM messages as shown above. Once this level is reached, the specific test case is fully defined as: a scenario where fully defined, REM messages are exchanged between a specific set participating entities, and where a specific set of additional requirements are imposed.

4.2 Adding new test cases to the test suite

The strategy followed for building the definitions of the test cases makes it easy to expand the test suite by incorporation of new test cases.

For defining a new test case the following steps are required:

- 1) Identify the **set of receiving entities**. If none of the predefined set of entities at the receiving side is the one required, define a new set as specified in clause 7.3. The sender is always present by default.

- 2) Define the REMSs that will participate in the test case.
 - 3) If the set of participating REMSs is not equal to none of the scenarios already identified in the present document, the new scenario will require to be defined in a new template.
 - 4) Identify the **sequence of actions** performed by each actor and their order of occurrence and assign a new unique identifier (<SCN_ID >) to the scenario.
 - 5) Identify **all the REM messages** generated by the actors as they go through the sequence of actions. For each message:
 - a) Identify its MIME sections.
 - b) For each MIME section identified different than the ERDS MIME sections, check if its header fields combination and the corresponding bodies have already been defined in the present document. If not, add the required combination of header fields and body values to the repertoire of named combinations to the section defining instances of the aforementioned MIME section as in the corresponding clauses (clauses 6.2.2, 6.2.3, 6.2.4.3, 6.2.4.4, 6.2.6 or 6.2.8).
 - c) List all the REM messages exchanged as parameters of the scenario.
 - d) Identify the ERDS evidence format and the set of ERDS evidence for each REM message including them and add the names of the ERDS evidence sets to the Var section of the template.
 - 6) Identify and define any other additional requirement for completely define the test case. If the set of requirements is different than all the sets already define, assign a name to it (<ADD_REQ_COMB>) and add it to the repertoire of named sets of additional requirements in Table 23 (clause 7.2).
-

5 Scenarios

5.1 Introduction

The present clause defines a number of selected scenarios that will be used in clause 8.

Clause 5.3 defines scenarios where sender and recipient(s) are subscribed to the same REMS.

Clause 5.4 defines scenarios where the sender and the recipient(s) are subscribed to different REMSs and there are not intermediate REMSs between them.

Clause 5.5 defines scenarios where sender is subscribed to a REMS and the recipient(s) is(are) not subscribed to the same REMS and there are one or more intermediate REMSs.

Unless anything said against it, all the scenarios assume that there are N entities at the receiving side.

Unless anything said against it, all the ERDS evidences that can contain details of different entities at the receiving side shall incorporate the details of the entire set of N entities at the receiving side.

Table 1 shows the template for defining one scenario.

Table 1: Template for the tabular definition of one scenario

Scenario id: <SCN_ID>			Purpose
Parameter: <REMS_receipt>_with_XML_SUB_REJ <Parameter 1 that helps to fully specify the scenario. Their number depends on the specific scenario>		Var EV_SET#1 = {..., ...}	
Parameter: <Parameter 2>		Var EV_SET#2 = {... ...}	
Parameter: <Parameter N>		Var EV_SET#N = {... ...}	
Sequence of actions			
<SEQUENCE OF ACTIONS. THERE IS ONE COLUMN PER PARTICIPATING ACTOR>			
#	Sender	REMS	Receiving side
The sequence is composed of a number of numerated steps, when the actors perform certain actions as shown below. Some frequent actions: send original message, accept submission, reject submission, consign, generate one ERDS evidence, generate one REM message, etc.			
1	Sender sends original message		
2		Rejects submission. Generates XML_SUB_REJ ERDS evidence	
3		Generates <REMS_receipt>_with_XML_SUB_REJ	
4		Sends <REMS_receipt>_with_XML_SUB_REJ	
5	Receives <REMS_receipt>_with_XML_SUB_REJ		

Each scenario is assigned a unique identifier <SCN_ID>. The reasons why the scenario has been defined are shown in column "Purpose".

The definition of each scenario requires that parties exchange a number of REM messages, which appear listed as parameters in the rows immediately below the headers row. Its number depends on the specific scenario.

Below the list of parameters the table shows a sequence of actions performed by different involved entities, which results in that a set of REM messages is generated and exchanged.

The definition of each scenario also can use a number of named ERDS evidence sets, which are listed in cells started with Var. Each ERDS evidence set is given a name EV_SET#<i>, being <i> a non-negative integer number.

The involved entities are sender (or sender's delegate, the scenario definition does not make any distinction between them), one or more REMSs, and the entities at the receiving side (for the same scenario there may be different sets of entities, for instance one recipient, one recipient's delegate, one or more recipients, or one or more recipients and one or more recipients' delegates).

Each step is assigned a positive integer number. The actions performed include: submission of messages, generation of REM messages, generation of ERDS evidence, acceptance of REM messages, rejection of REM messages, consignment of REM messages, retrieval of REM messages by entities at receiving side, failures, etc.

5.2 Abbreviations used in tables defining scenarios

The present clause shows some abbreviations (which have already been anticipated in clause 3.3 which have already been anticipated in clause 3.3) used in the tables that define the scenarios.

Table 2 shows the abbreviations used for the different ERDS evidence.

Table 2: ERDS evidence abbreviations

ERDS Evidence name	ERDS Evidence abbreviation
SubmissionAcceptance	SUB_ACC
SubmissionRejection	SUB_REJ
RelayAcceptance	REL_ACC
RelayRejection	REL_REJ
RelayFailure	REL_FAIL
NotificationForAcceptance	NOT_F_ACC
NotificationForAcceptanceFailure	NOT_F_ACC_FAIL
ConsignmentAcceptance	CONS_ACC
ConsignmentRejection	CONS_REJ
AcceptanceRejectionExpiry	ACC_REJ_EXP
ContentConsignment	CONT_CONS
ContentConsignmentFailure	CONT_CONS_FAIL
ConsignmentNotification	CONS_NOT
ConsignmentNotificationFailure	CONS_NOT_FAIL
ContentHandover	CONT_HAND
ContentHandoverFailure	CONT_HAND_FAIL
RelayToNonERDS	REL_T_NERDS
RelayToNonERDSFailure	REL_T_NERDS_FAIL
ReceivedFromNonERDS	REC_F_NERDS

ETSI EN 319 522-1 [1] specify a XML format for ERDS evidence, but also allows that they are PDF documents. The present document differentiates both cases using a prefix for the ERDS evidence abbreviations as follows:

- **XML_** prefix indicates that the identified object is a XML ERDS evidence.
- **PDF_** prefix that the identified object is a PDF ERDS evidence.

EXAMPLE: The abbreviation for the XML SubmissionAcceptance ERDS evidence will be **XML_SUB_ACC**.
The abbreviation for the PDF SubmissionAcceptance ERDS evidence will be **PDF_SUB_ACC**.

The tables defining the Scenarios use the following abbreviations for the different participating REMSs:

- **SREMS** stands for the REMS serving the sender, in the scenarios where it is different from the REMS serving the entities at receiving side.
- **RREMS** stands for the REMS serving the entities at receiving side, in the scenarios where it is different from the REMS serving the sender.
- **IREMS** stands for a REMS that directly serves neither the sender nor the recipient(s)/recipient's delegate, but instead is an intermediate REMS that relays REM messages from SREMS to RREMS and from RREMS to SREMS.

5.3 Black-box model scenarios

5.3.1 Introduction

This clause defines scenarios where the sender and the entities at the receiving side are subscribed to the same REMS and consequently REM messages are not relayed between different REMSs.

Clause 5.3.2 defines scenarios where the REMS operates in Store and Forward style.

Clause 5.3.3 defines scenarios where the REMS operates in Store and Notify style.

5.3.2 Scenarios for Store and Forward style

Table 3 defines a number of scenarios for the case where sender and the entities at receiving side are subscribed to the same REMS operating in Store and Forward style.

Table 3: Scenarios for intra-REMS operating in Store and Forward style (1/13)

Scenario id: REMS_SF#1				Purpose
Parameter: <REMS_receipt>_with_XML_SUB_REJ				The simplest negative scenario: The sender sends the original message to one entity. The REMS rejects the original message submitted by the sender because of one reason, and sends back a REM receipt with the SubmissionRejection ERDS evidence (<REMS_receipt>_with_XML_SUB_REJ).
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Rejects submission. Generates SUB_REJ ERDS evidence with details of the N recipients		
3		Generates <REMS_receipt>_with_XML_SUB_REJ		
4		Sends REMS receipt to the sender		
5	Receives REMS receipt			

NOTE 1: As it has been anticipated, negative scenarios like this one do not mention the reason for failure. This is a separated parameter for the test case definition in clause 8.

Table 3a: Scenarios for intra-REMS operating in Store and Forward style (2/13)

Scenario id: REMS_SF#2				Purpose
Parameter: <REMS_receipt>_with_XML_SUB_REJ		Var EV_SET#1 = {2 XML_SUB_REJ }		Modified scenario REMS_SF#1: The sender sends the original message to N different entities. The REMS rejects the original message submitted by the sender because of one reason for M entities at the receiving side and because of another reason for the other N-M entities. It generates two SubmissionRejection ERDS evidences and sends back a REM receipt with these two SubmissionRejection ERDS evidences (<REMS_receipt>_with_XML_SUB_REJ).
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Rejects submission. Generates 2 XML_SUB_REJ ERDS evidences. One of them with details of M entities; the other with details of N-M entities		
3		Generates <REMS_receipt>_with the 2_ aforementioned XML_SUB_REJ		
4		Sends REMS receipt to the sender		
5	Receives REMS receipt			

Table 3b: Scenarios for intra-REMS operating in Store and Forward style (3/13)

Scenario id: REMS_SF#3				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC , XML_CONT_CONS}		The simplest successful scenario:
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				The sender sends the original message to several entities. The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and consigns them to the receiving entities. After that the REMS generates and sends back to the sender a REM receipt with one SubmittingAcceptance ERDS evidence and one ContentConsignment ERDS evidence (<REMS_receipt>_with_EV_SET#1) to the sender. Each evidence includes the details of all the (N) entities at receiving side.
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch>_with_XML_SUB_ACC for the N receiving entities		
4		Consigns REM dispatch to receiving side		
5		Generates one XML_CONT_CONS ERDS evidence with details of the N recipients	<REM_dispatch>_with_XML_SUB_ACC consigned to receiving side	
6		Generates <REMS_receipt>_with_EV_SET#1		
7		Sends it back to sender		
8	Receives <REMS_receipt>_with_EV_SET#1			

Table 3c: Scenarios for intra-REMS operating in Store and Forward style (4/13)

Scenario id: REMS_SF#4				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC , XML_CONT_CONS, XML_CONT_CONS_FAIL}		As scenario REMS_SF#3 but now one of the N consignments fails:
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				<p>The sender sends the original message to N entities.</p> <p>The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and tries to consign them to the receiving entities, but now one consignment fails, which implies the generation of 1 XML_CONT_CONS_FAIL ERDS evidence.</p> <p>The REMS generates a REMS receipt reporting the acceptance of submission, the successful consignment of N-1 REM dispatches and the failure of 1 REM dispatch (<REMS_receipt>_with_EV_SET#1).</p>
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch>_with_XML_SUB_ACC for the N receiving entities		
4		Consigns REM dispatch to receiving side		
5		Generates one XML_CONT_CONS ERDS evidence with details of the N-1 entities AND one XML_CONT_CONS_FAIL with details of one entity	N-1 <REM_dispatch>_with_XML_SUB_AC C consigned to receiving side 1 fails	
6		Generates <REMS_receipt>_with_EV_SET#1		
7		Sends it back to sender		
8	Receives <REMS_receipt>_with_EV_SET#1			

Table 3d: Scenarios for intra-REMS operating in Store and Forward style (5/13)

Scenario id: REMS_SF#5				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC , XML_CONT_CONS, 2 XML_CONT_CONS_FAIL}		As scenario REMS_SF#3 but now two consignments fail, and each one for different reason, which implies the generation of two XML_CONT_CONS_FAIL ERDS evidences:
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		The sender sends the original message to N entities.
3		Generates <REM_dispatch>_with_XML_SUB_ACC for the N receiving entities		The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence
4		Consigns REM dispatch to receiving side		
5		Generates one XML_CONT_CONS ERDS evidence with details of the N-2 entities AND 2 XML_CONT_CONS_FAIL with details of one entity	N-2 <REM_dispatch>_with_XML_SUB_AC C consigned to receiving side The other 2 fail, each one for a different reason	
6		Generates <REMS_receipt>_with_EV_SET#1		
7		Sends it back to sender		
8	Receives <REMS_receipt>_with_EV_SET#1			(<REM_dispatch>_with_XML_S UB_ACC), and tries to consign them to the receiving entities, but now two consignment fail, each one by a different reason. The REMS generates a REMS receipt reporting the acceptance of submission, the successful consignment of N-2 REM dispatches and the failure of 2 REM dispatches, which include 2 ERDS evidence (<REMS_receipt>_with_EV_SE T#1, which include 2 XML_CONT_CONS_FAIL).

Table 3e: Scenarios for intra-REMS operating in Store and Forward style (6/13)

Scenario id: REMS_SF#6				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND}		Successful scenario: The sender sends the original message to N entities.
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N entities. After the successful consignment, all the entities at the receiving side successfully retrieve the messages. The REMS generates a REMS receipt (<REMS_receipt>_with_EV_SET#1) with following ERDS evidence: one SubmissionAcceptance, one ContentConsignment, and one ContentHandover. Each ERDS evidence includes the details of all the (N) entities at the receiving side.
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch>_with_XML_SUB_ACC		
4		Consigns them to the receiving side		
5		Generates one XML_CONT_CONS ERDS evidence with details of the N recipients	N <REM_dispatch>_with_XML_SUB_AC C consigned to receiving side	
6			All the entities retrieve the REM dispatch	
7		Generates one XML_CONT_HAND ERDS evidence with details of the N recipients	N <REM_dispatch>_with_XML_SUB_AC C handed over to receiving side	
8		Generates <REMS_receipt>_with_EV_SET#1		
9	Receives <REMS_receipt>_with_EV_SET#1			

NOTE 2: The former scenarios explicitly mention in the Sequence of Actions columns that the ERDS evidences include details of the N recipients. As it has been anticipated above, hereinafter the absence of such explicit mention will be interpreted as an explicit mention of this fact. Explicit details will appear wherever this is not true.

Table 3f: Scenarios for intra-REMS operating in Store and Forward style (7/13)

Scenario id: REMS_SF#7				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, XML_CONT_HAND_FAIL}		As scenario REMS_SF#3 but now the handover of the REM dispatch is performed, and one of the handing over fails:
Parameter: REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			The sender sends the original message to several entities.
2		Accepts submission. Generates one XML_SUB_ACC ERDS evidence		The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N receiving entities.
3		Generates <REM_dispatch>_with_XML_SUB_ACC		
4		Consigns them to the receiving side		N-1 receiving entities successfully hand over the REM dispatch, but 1 entity fails.
5		Generates one XML_CONT_CONS ERDS evidence	<REM_dispatch>_with_XML_SUB_ACC consigned to receiving side	
6			Entities try to retrieve the REM dispatch, but one fails	The REMS generates an ERDS receipt (<REMS_receipt>_with_EV_SET#1) with following ERDS evidence: one SubmissionAcceptance, one ContentConsignment, one ContentHandover, and one ContentHandoverFailure.
7		Generates one XML_CONT_HAND ERDS one evidence for N-1 entities and one XML_CONT_HAND_FAIL ERDS evidence for one entity	N-1 <REM_dispatch>_with_XML_SUB_ACC handed over to receiving side. One fails	
8		Generates <REMS_receipt>_with_EV_SET#1		Each evidence includes the details of the entire set of recipient entities affected by the event that it reports, namely: <ul style="list-style-type: none"> XML_SUB_ACC includes details of the N entities at the receiving side; XML_CONT_CONS includes details of the N entities at the receiving side; XML_CONT_HAND includes details of the N-1 entities that the service handed over the message to; XML_CONT_HAND_FAIL includes the details of the entity that the service could not hand over the message to.
9	Receives <REMS_receipt>_with_EV_SET#1			

Table 3g: Scenarios for intra-REMS operating in Store and Forward style (8/13)

Scenario id: REMS_SF#8			Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, 2 XML_CONT_HAND_FAIL}	As scenario REMS_SF#3 but now the handover of the REM dispatch is performed, and two of the handing overs fail for different reasons.
Parameter: REMS_receipt>_with_EV_SET#1			
Sequence of actions			
#	Sender	REMS	Receiving side
1	Sender sends original message		The sender sends the original message to N entities.
2		Accepts submission. Generates one XML_SUB_ACC ERDS evidence	The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N receiving entities.
3		Generates <REM_dispatch>_with_XML_SUB_ACC	
4		Consigns them to the receiving side	N-2 receiving entities successfully hand over the REM dispatch, but 2 entities fail.
5		Generates one XML_CONT_CONS ERDS evidence	
6			Entities try to retrieve the REM dispatch, but one fails
7		Generates one XML_CONT_HAND ERDS one evidence for N-2 entities and 2 XML_CONT_HAND_FAIL ERDS evidences, each one for a different entity	N-2 <REM_dispatch>_with_XML_SUB_ACC handed over to receiving side. Two of them fail
8		Generates <REMS_receipt>_with_EV_SET#1	

Scenario id: REMS_SF#8				Purpose
9	Receives <REMS_receipt>_with_EV_SET#1			<p>The REMS generates an ERDS receipt (<REMS_receipt>_with_EV_SET#1) with the following ERDS evidence: one SubmissionAcceptance, one ContentConsignment, one ContentHandover, and two ContentHandoverFailure.</p> <p>Each evidence includes the details of the entire set of recipient entities affected by the event that it reports, namely:</p> <ul style="list-style-type: none"> • XML_SUB_ACC includes details of the N entities at the receiving side; • XML_CONT_CONS includes details of the N entities at the receiving side; • XML_CONT_HAND includes details of the N-2 entities that the service handed over the message to; • Each one of the two XML_CONT_HAND_FAIL ERDS evidence includes the details of the entity that the service could not hand over the message to with the reasons for not handing over.

Hereinafter, the scenarios do not show handing over, but only consignment. However, a set of scenarios including handing over could be easily built based on them.

Table 3h: Scenarios for intra-REMS operating in Store and Forward style (9/13)

Scenario id: REMS_SF#9				Purpose
Parameter: <REM_dispatch>		Var EV_SET#1 = {XML_SUB_ACC,XML_CONS_NOT,XML_CONT_CONS}		As scenario REMS_SF#3 but now the REMS sends a REMS notification of consignment to receiving side.
Parameter: <REMS_notification>_of_Consignment				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				The sender sends the original message to N entities. The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N receiving entities. The REMS generates N notifications of consignment (<REMS_notification>_of_Consignment) for the receiving entities and sends them. The REMS generates one REMS receipt (<REMS_receipt>_with_EV_SET#1) with the following ERDS evidence: one SubmissionAcceptance, one ContentConsignment, and one ContentConsignmentNotification.
#	Sender	REMS	Receiving side	
1	Sender sends the original message			
2		Accepts submission. Generates one XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch>_with_XML_SUB_ACC		
4		Consigns <REM_dispatch>_with_XML_SUB_ACC to receiving side		
5			N <REM_dispatch>_with_XML_SUB_ACC consigned to receiving side	
6		Generates one XML_CONT_CONS ERDS evidence		
7		Generates <REMS_notification>_of_Consignment for N entities		
8		Sends consignment notification to receiving side		
9		Generates one XML_CONS_NOT ERDS evidence for N entities	<REMS_notification>_of_Consignment received by receiving side	
10		Generates <REMS_receipt>_with_EV_SET#1		
11		Sends it to the sender		
12	Receives <REMS_receipt>_with_XML_XML_EV_SET#1			Each evidence includes the details of the entire set of recipient entities affected by the event that it reports, namely: <ul style="list-style-type: none"> XML_SUB_ACC includes details of the N entities at the receiving side; XML_CONT_CONS_NOT includes details of the N entities at the receiving side; XML_CONT_CONS includes details of the N entities at the receiving side.

Table 3i: Scenarios for intra-REMS operating in Store and Forward style (10/13)

Scenario id: REMS_SF#10			Purpose	
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, XML_CONS_NOT_FAIL }	As scenario REMS_SF#3 but now REMS sends notifications of consignment and one of the REMS consignment notifications fails.	
Parameter: <REMS_notification>_of_Consignment				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions			The sender sends the original message to N entities. The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N receiving entities. The REMS generates N notifications of consignment (<REMS_notification>_of_Consignment) for the receiving entities and sends them, but one fails. The REMS generates one REMS receipt (<REMS_receipt>_with_EV_SET#1) with the following ERDS evidence: one SubmissionAcceptance, one	
#	Sender	REMS		Receiving side
1	Sender sends the original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates N <REM_dispatch>_with_XML_SUB_ACC		
4		Consigns REM dispatch to the receiving side		N <REM_dispatch>_with_XML_SUB_A CC consigned to receiving side
5		Generates <REMS_notification>_of_Consignment for N entities		REM dispatch with the original message AND REMS receipt consigned to recipient
6		Tries to send N <REMS_notification>_of_Consignment but one fails.		
7		Generates one XML_CONS_NOT ERDS evidence for N-1 entities (the N-1 whose notifications were sent) and one XML_CONS_NOT_FAIL ERDS evidence corresponding to the notification that failed		N-1 <REMS_notification>_of_Consignmen t are received successfully; 1 fails
8		Generates <REMS_receipt>_with_EV_SET#1		

Scenario id: REMS_SF#10			Purpose
9	Receives <REMS_receipt>_with_EV_SET#1		<p>ContentConsignment, one ContentConsignmentNotification, and one ContentConsignmentNotificationFailure.</p> <p>Each evidence includes the details of the entire set of recipient entities affected by the event that it reports, namely:</p> <ul style="list-style-type: none"> • XML_SUB_ACC includes details of the N entities at the receiving side; • XML_CONT_CONS_NOT includes details of the N-1 entities at the receiving side to whom the REMS has sent a consignment notification; • XML_CONT_CONS includes details of the N entities at the receiving side; • XML_CONT_CONS_NOT_FAIL including details of the entity at the receiving side for whom the notification has failed and the reason for failure.

Table 3j: Scenarios for intra-REMS operating in Store and Forward style (11/13)

Scenario id: REMS_SF#11			Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC	Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, 2 XML_CONS_NOT_FAIL }		As scenario REMS_SF#3 but now REMS sends notifications of consignment and two of the REMS consignment notifications fail due to different reasons. This implies the generation of two XM_CONST_NOT_FAIL ERDS evidences.
Parameter: <REMS_notification>_of_Consignment			
Parameter: <REMS_receipt>_with_EV_SET#1			
Sequence of actions			
#	Sender	REMS	Receiving side
1	Sender sends the original message		
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence	
3		Generates N <REM_dispatch>_with_XML_SUB_ACC	
4		Consigns REM dispatch to the receiving side	N <REM_dispatch>_with_XML_SUB_ACC consigned to receiving side
5		Generates <REMS_notification>_of_Consignment for N entities	REM dispatch with the original message AND REMS receipt consigned to recipient
6		Sends N <REMS_notification>_of_Consignment but 2 of them fail.	
			The sender sends the original message to N entities.
			The REMS accepts the submission of the original message, generates as many REM dispatches as required by the number of entities in the receiving side, enclosing the original message and the SubmissionAcceptance ERDS evidence (<REM_dispatch>_with_XML_SUB_ACC), and successfully consigns them to the N receiving entities.

7		Generates 1 XML_CONS_NOT_FAIL ERDS evidence for two entities and one XML_CONS_NOT ERDS evidence for N-2 entities	N-2<REMS_notification>_for Consignment are received successfully; 2 <REMS_notification>_for Consignment fail	The REMS generates N notifications of consignment (<REMS_notification>_of_Consignment) for the receiving entities and sends them, but two of them fail.
8		Generates <REMS_receipt>_with_EV_SET#1		The REMS generates one REMS receipt (<REMS_receipt>_with_EV_SET#1) with the following ERDS evidence: one SubmissionAcceptance, one ContentConsignment, one ContentConsignmentNotification, and one ContentConsignmentNotificationFailure.
9	Receives <REMS_receipt>_with_EV_SET#1			<p>Each evidence includes the details of the entire set of recipient entities affected by the event that it reports, namely:</p> <ul style="list-style-type: none"> • XML_SUB_ACC includes details of the N entities at the receiving side; • XML_CONT_CONS_NOT includes details of the N-2 entities at the receiving side; • XML_CONT_CONS includes details of the N entities at the receiving side; • XML_CONT_CONS_NOT_FAIL includes details of 2 the entities at the receiving side that did not receive the consignment notification.

Table 3k: Scenarios for intra-REMS operating in Store and Forward style (12/13)

Scenario id: REMS_SF#12			Purpose	
Parameter: <REM_payload>		Var EV_SET#1 = {XML_SUB_ACC, XML_CONT_CONS}		
Parameter: <REMS_receipt_1>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_2>_with_XML_EV_SET#1				
Parameter: <REMS_receipt>_with_EV_SET#1			As scenario REMS_SF#3 but now the original message and the ERDS evidence travel in different REM messages to the receiving side.	
#	Sender	REMS		Receiving side
1	Sender sends the original message			
2		Accepts submission. Generates one XML_SUB_ACC ERDS evidence		
3		Generates <REM_payload>		
4		Generates <REMS_receipt_1>_with_XML_SUB_ACC		
5		Consigns <REM_payload> and <REMS_receipt_1>_with_XML_SUB_ACC to the receiving side		
6		Generates one XML_CONT_CONS ERDS evidence		<REM_payload>AND <REMS_receipt_1>_with_XML_SUB_A CC consigned to receiving side
7		Generates <REMS_receipt_2>_with_EV_SET#1		
8	Receives <REMS_receipt_2>_with_EV_SET#1	Sends it to the sender		

NOTE 3: It is possible to define a set of scenarios covering different types of failures in consignment and/or handover, and/or notifications as for the former test cases where ERDS evidences and original messages travelled together within REM dispatches.

Table 3I: Scenarios for intra-REMS operating in Store and Forward style (13/13)

Scenario id: REMS_SF#13				Purpose
Parameter: <REM_payload>				As scenario REMS_SF#3 but now the REMS generates and sends an REMS receipt as soon as it generates the corresponding ERDS Evidence.
Parameter: <REMS_receipt>_with_XML_SUB_ACC				
Parameter: <REMS_receipt>_with_XML_CONT_CONS				
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REMS_receipt>_with_XML_SUB_ACC and sends it to both sender and receiving side		
4		Sends <REMS_receipt>_with_XML_SUB_ACC to both sender and receiving side		
5	Sender receives <REMS_receipt>_with_XML_SUB_ACC		Entities in receiving side receive <REMS_receipt>_with_XML_SUB_ACC	
6		Generates <REM_payload>_ for the N receiving entities		
7		Consigns REM payload to receiving side		
8		Generates one XML_CONT_CONS ERDS evidence with details of the N recipients	<REM_payload>_ to receiving side	
9		Generates <REMS_receipt>_with_XML_CONT_CONS		
10		Sends <REMS_receipt>_with_XML_CONT_CONS back to sender		
11	Receives <REMS_receipt>_with_XML_CONT_CONS			

NOTE 4: It is possible to define a set of scenarios where:

- 1) each time the REMS generates an ERDS evidence, it generates and sends an <ERDS receipt> immediately after; and
- 2) the original message travels within an <REM payload>.

This set would cover different types of failures in consignment and/or handover, and/or notifications as for the former test cases where ERDS evidences and original messages travelled together within REM dispatches.

5.3.3 Scenarios for Store and Notify style

Table 4 defines a number of scenarios for the case where sender and the entities at receiving side are subscribed to the same REMS operating in Store and Notify style.

Table 4: Scenarios for intra-REMS operating in Store&Notify model of operation (1/4)

Scenario id: REMS_SN#1			Purpose	
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = { XML_NOT_F_ACC ERDS, XML_CONS_ACC, XML_CONT_CONS}	First scenario for Store&Notify style, where the REMS asks to receiving side for acceptance, and all the entities at receiving side accept.	
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS		Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REMS_notification>_for_Acceptance		
4		Sends <REMS_notification>_for_Acceptance		
5				All entities in receiving side receive one <REMS_notification>_for_Acceptance and answer positively
6		Generates XML_NOT_F_ACC ERDS evidence		
7		Receives positive responses from receiving side and generates XML_CONS_ACC ERDS evidence for the N entities at receiving side		
8		Generates <REM_dispatch>_with_XML_SUB_ACC		
9		Consigns N <REM_dispatch>_with_XML_SUB_ACC		
10		Generates XML_CONT_CONS ERDS evidence	N <REM_dispatch>_with_XML_SUB_ACC consigned to receiving side	
11		Generates <REMS_receipt>_with_EV_SET#1		
12	Receives <REMS_receipt>_with_EV_SET#1			

Table 4a: Scenarios for intra-REMS operating in Store&Notify model of operation (2/4)

Scenario id: REMS_SN#2			Purpose	
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_NOT_F_ACC, XML_CONS_ACC, XML_CONS_REJ, XML_CONT_CONS}	As before but one of the entities at the receiving side does not accept consignment.	
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS		Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates N <REMS_notification>_for_Acceptance		
4		Sends N <REMS_notification>_for_Acceptance		
5		Generates one XML_NOT_F_ACC ERDS evidence for N entities		Each entity receives one <REMS_notification>_for_Acceptance. N-1 answer positively, one answers negatively
6		Receives N-1 positive answers and one negative answer		
7		Generates one XML_CONS_ACC ERDS evidence for N-1 entities and one XML_CONS_REJ ERDS evidence		
8		Generates one <REM_dispatch>_with_XML_SUB_ACC		
9		Consigns it to the N-1 entities at receiving side		
10		Generates XML_CONT_CONS for N-1 entities	<REM_dispatch>_with_XML_SUB_ACC consigned to N-1 entities at receiving side	
11		Generates <REMS_receipt>_with_EV_SET#1		
12		Sends it to sender		
13	Receives <REMS_receipt>_with_EV_SET#1			

Table 4b: Scenarios for intra-REMS operating in Store&Notify model of operation (3/4)

Scenario id: REMS_SN#3				Purpose
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_NOT_F_ACC , XML_ACC_REJ_EXP, XML_CONS_ACC, XML_CONT_CONS }		As before but one of the entities at the receiving side does not answer in time.
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS	Receiving side	
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates N <REMS_notification>_for_Acceptance		
4		Sends <REMS_notification>_for_Acceptance to N entities		
5		Generates one XML_NOT_F_ACC ERDS evidence for N entities	Each entity receives one <REMS_notification>_for_Acceptance. N-1 answer positively, one does not answer in time	
6		Receives N-1 positive answers		
7		When the expiration time is reached generates <REM_dispatch>_with_XML_SUB_ACC for N-1 entities		
		Consigns them to the N-1 entities that have accepted		
		Generates one XML_CONS_ACC ERDS evidence for N-1 entities and one XML_ACC_REJ_EXP ERDS evidence for one entity	N-1 entities at receiving side receive the <REM_dispatch>_with_XML_SUB_ACC	
8		Generates <REMS_receipt>_with_EV_SET#1		
9		Sends it to the sender		
10	Receives <REMS_receipt>_with_EV_SET#1			

Table 4c: Scenarios for intra-REMS operating in Store&Notify model of operation (4/4)

Scenario id: REMS_SN#4			Purpose	
Parameter: <REM_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = { XML_NOT_F_ACC, XML_CONT_HAND }	First scenario for Store&Notify style, where the REMS asks to receiving side for acceptance, and all the entities at receiving side accept.	
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt>_with_EV_SET#1				
Sequence of actions				
#	Sender	REMS		Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
		Generates <REMS Receipt> with XML_SUB_ACC ERDS		
		Sends back <REMS Receipt> with XML_SUB_ACC ERDS evidence to sender		
3	Sender receives <REMS Receipt> with XML_SUB_ACC ERDS evidence	Generates N <REMS_notification>_for Acceptance		
4		Sends N <REMS_notification>_for Acceptance		
5			All entities in receiving side receive one <REMS_notification>_for Acceptance	
6		Generates XML_NOT_F_ACC ERDS evidence for N entities	All entities in receiving side and answer positively to the N <REMS_notification>	
7		Receives positive responses from receiving side	All entities in receiving retrieve the REM dispatch	
8		Generates one XML_CONT_HAND ERDS evidence with details of the N recipients		
9		Generates <REMS_receipt>_with_EV_SET#1		
		Sends <REMS_receipt>_with_EV_SET#1 back to the sender		
10	Receives <REMS_receipt>_with_EV_SET#1			

5.4 Scenarios for 4-corner model

5.4.1 Introduction

The present clause defines test cases for scenarios that take place when the sender and the entities at the receiving side are subscribed to different REMSs but there are not intermediate REMSs between the SREMS and the RREMSs.

Clause 5.4.2 defines test cases when both REMSs operate in Store and Forward style.

Clause 5.4.3 defines test cases when the SREMS operates Store and Forward style and the RREMS operates Store and Notify style.

Clause 5.4.4 defines test cases when the SREMS operates Store and Notify style and the RREMS operates Store and Forward style.

5.4.2 Scenarios for Store&Forward to Store&Forward

Table 5 defines a number of scenarios for the case where SREMS and RREMS operate both Store and Forward style and are NOT the same REMS.

The scenarios are based on scenarios in Table 3 adding the relay acceptance and relay rejection events at the some of the RREMSs and their corresponding ERDS evidences.

For the sake of simplicity, it will suppose that all the entities at receiving side are served by the same RREMS. It could be possible to use the templates defined in the present document for defining scenarios where the aforementioned entities are served by different RREMSs.

Table 5: Scenarios for SREMS and RREMSs operating Store&Forward (1/7)

Scenario id: SREMS_SF_RREMS_SF#1					Purpose
Parameter: <REMS_receipt_1>_with_XML_SUB_ACC					The simplest scenario: the SREMS rejects the original message from the user.
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Rejects submission. Generates XML_SUB_REJ ERDS evidence			
3		Generates <REMS_receipt>_with_XML_SUB_REJ			
4		Sends the <REMS_receipt>_with_XML_SUB_REJ to the sender			
5	Sender receives <REMS_receipt>_XML_SUB_REJ				

Table 5a: Scenarios for SREMS and RREMSs operating Store&Forward (2/7)

Scenario id: SREMS_SF_RREMS_SF#2					Purpose
Parameter: <REMS_dispatch>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_SUB_ACC, XML_REL_REJ}			Another simple scenario: the RREMS rejects the REM dispatch relayed by the SREMS and sends back a REM receipt with one RelayRejection ERDS evidence.
Parameter: <REMS_receipt_1>_with_XML_REL_REJ					
Parameter: <REMS_receipt_2>_with_EV_SET#1					
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch>_with_XML_SUB_ACC			
4		Relays the <REM_dispatch>_with_XML_SUB_ACC to the RREMS			
5			The RREMSs Rejects the <REM_dispatch>_with_XML_SUB_ACC		
6			Generates XML_REL_REJ ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_REJ		

8			Sends <REMS_receipt_1>_with_XML_REL_REJ to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL _REJ			
10		Generates <REMS_receipt_2>_with_EV_SET#1			
11		Sends it back to sender			
12	Sender receives <REMS_receipt_2>_with_EV_S ET#1				

Table 5b: Scenarios for SREMS and RREMSs operating Store&Forward (3/7)

Scenario id: SREMS_SF_RREMS_SF#3					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC					The simplest successful scenario: the SREMS accepts the submission of the original message, generates one REM dispatch and relays to RREMS. This accepts relay, builds its own REM dispatch and delivers it to the N recipients in receiving side. SREMS generates and sends back to the sender a REM receipt with one SubmissionAcceptance ERDS evidence, one RelayAcceptance, and one ContentConsignment ERDS evidence. Clause 4.3.2.1 of ETSI EN 319 532-1 [3] shows a variation of this scenario where RREMS sends XML_REL_ACC and XML_CONT_CONS in different REM receipts.
Parameter: <REMS_receipt_1>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_2>_with_XML_REL_ACC					
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_3>_with_XML_CONT_CONS					
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REMS_receipt_1>_with_XML_SUB_ACC and sends it to the sender			
4	Receives <REMS_receipt_1>_with_XML_SUB_ACC	Generates <REM_dispatch_1>_with_XML_SUB_ACC			
5		Relays it to RREMS REM dispatch to recipient			
6			Accepts it and generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_2>_with_XML_REL_ACC		
8			Sends <REMS_receipt_2>_with_XML_REL_ACC to SREMS		
9		Receives <REMS_receipt_2>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
10			Consigns it to the receiving side		

Scenario id: SREMS_SF_RREMS_SF#3				Purpose
11			Generates XML_CONT_CONS ERDS evidence	
12			Generates <REMS_receipt_3>_with_XML_CONT_CONS	
13			Sends it back to the SREMS	
14		Receives <REMS_receipt_3>_with_XML_CONT_CONS and sends it back to the sender		
15	Receives <REMS_receipt_3>_with_XML_CONT_CONS			

Table 5c: Scenarios for SREMS and RREMSs operating Store&Forward (4/7)

Scenario id: SREMS_SF_RREMS_SF#4				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {REL_ACC, CONT_CONS}		As scenario SREMS_SF_RREMS_SF#3 but now finalized with hand over and RelayAcceptance and ContentConsignment travel together in the same REM receipt back to SREMS.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_1>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_2>_with_EV_SET#1				
Parameter: <REMS_receipt_3>_with_XML_CONT_HAND				
Sequence of actions				
#	Sender	REMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REMS_receipt_1>_with_XML_SUB_ACC and sends it to the sender		
4	Receives <REMS_receipt_1>_with_XML_SUB_ACC	Generates <REM_dispatch_1>_with_XML_SUB_ACC		
5		Relays <REM_dispatch_1>_with_XML_SUB_ACC TO RREMS		
6			Accepts it and generates XML_REL_ACC ERDS evidence	
7			Generates <REM_dispatch_2>_with_XML_SUB_ACC	
8			Consigns it to the receiving side	

Scenario id: SREMS_SF_RREMS_SF#4					Purpose
9			Generates XML_CONT_CONS ERDS evidence	<REM_dispatch_2>_with_XML_SUB_ACC is consigned to all the entities at receiving side	
10			Generates <REMS_receipt_2>_with_EV_SET#1		
11			Send <REMS_receipt_2>_with_EV_SET#1 to SREMS	Entities in receiving side retrieve user content	
12		Receives <REMS_receipt_2>_with_EV_SET#1 and sends it back to the sender	Generates XML_CONT_HAND ERDS evidence		
13	Receives <REMS_receipt_2>_with_EV_SET#1		Generates <REMS_receipt_3>_with_XML_CONT_HAND		
14			Sends <REMS_receipt_3>_with_XML_CONT_HAND to SREMS		
15		Receives <REMS_receipt_3>_with_XML_CONT_HAND and sends it back to the sender			
16	Receives <REMS_receipt_3>_with_XML_CONT_HAND				

Table 5d: Scenarios for SREMS and RREMSs operating Store&Forward (5/7)

Scenario id: SREMS_SF_RREMS_SF#5					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {XNL_REL_ACC,XML_CON_CONS}			As the previous scenario but now one of the handing over fails. Hereinafter, the scenarios do not show handing over, but only consignment. However, a set of scenarios including handing over could be easily built based on them.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC		Var EV_SET#2 = {XML_CONT_HAND_FAIL}			
Parameter: <REMS_receipt_1>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_2>_with_EV_SET#1					
Parameter: <REMS_receipt_3>_with_EV_SET#2					
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REMS_receipt_1>_with_XML_SUB_ACC and sends it to the sender			

Scenario id: SREMS_SF_RREMS_SF#5				Purpose
4	Receives <REMS_receipt_1>_with_XML_SUB_ACC	Generates <REM_dispatch_1>_with_XML_SUB_ACC		
5		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
6			Accepts it and generates XML_REL_ACC ERDS evidence	
7			Generates <REM_dispatch_2>_with_XML_SUB_ACC	
8			Consigns it to the receiving side	
9			Generates XML_CONT_CONS ERDS evidence	<REM_dispatch_2>_with_XML_SUB_ACC is consigned to all the entities at receiving side
10			Generates <REMS_receipt_2>_with_EV_SET#1	
11			Send <REMS_receipt_2>_with_EV_SET#1 to SREMS	Entities in receiving side retrieve user content. N-1 succeed. One fails.
12		Receives <REMS_receipt_2>_with_EV_SET#1 and sends it back to the sender	Generates one XML_CONT_HAND ERDS evidence for N-1 entities and one XML_CONT_HAND_FAIL ERDS evidence for one entity	
13	Receives <REMS_receipt_2>_with_EV_SET#1		Generates <REMS_receipt_3>_with_EV_SET#2	
14			Sends <REMS_receipt_3>_with_EV_SET#2 to SREMS	
15		Receives <REMS_receipt_3>_with_EV_SET#2 and sends it back to the sender		
16	Receives <REMS_receipt_3>_with_EV_SET#2			

Table 5e: Scenarios for SREMS and RREMSs operating Store&Forward (6/7)

Scenario id: SREMS_SF_RREMS_SF#6		Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC	Var EV_SET#1 = {CONT_CONS, CON_CONS_FAIL}	As scenario
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC		SREMS_SF_RREMS_SF#3 but

Scenario id: SREMS_SF_RREMS_SF#6				Purpose	
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				now one of the REM dispatch consignments fails.	
Parameter: <REMS_receipt_2>_with_EV_SET#1					
Sequence of actions					
#	Sender	SREMS	RREMS		Receiving side
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to RREMS			
5			Accepts it and generates XML_REL_ACC ERDS evidence		
6			Generates <REMS_receipt_1>_with_XML_REL_ACC		
7			Sends <REMS_receipt_1>_with_XML_REL_ACC to SREMS		
8		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
9			Consigns it to receiving side. One fails.		
10					<REM_dispatch_2>_with_XML_SUB_ACC consigned to N-1 entities in receiving side. The other consignment fails
11			Generates one XML_CONT_CONS ERDS evidence related to N-1 entities Generates one XML_CONT_CONS_FAIL related to one entity		
12			Generates <REMS_receipt_2>_with_EV_SET#1		
13			Sends it back to the SREMS		
14		Receives <REMS_receipt_2>_with_EV_SET#1 and sends it back to the sender			
15	Receives <REMS_receipt_2>_with_EV_SET#1				

Table 5f: Scenarios for SREMS and RREMSs operating Store&Forward (7/7)

Scenario id: SREMS_SF_RREMS_SF#7					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC					In this scenario the consignment is performed but the SREMS does not receive any information on consignment from RREMS within a predefined period of time.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_1>_with_XML_REL_ACC					
Parameter: <REMS_receipt_2>_with_XML_CONT_CONS_FAIL					
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to RREMS			
5			Accepts it and generates XML_REL_ACC ERDS evidence		
6			Generates <REMS_receipt_1>_with_XML_REL_ACC		
7			Sends <REMS_receipt_1>_with_XML_REL_ACC to SREMS		
8		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
9			Consigns it to receiving side		
10				<REM_dispatch_2>_with_XML_SUB_ACC consigned to N entities in receiving side	
11			Something goes wrong and RREMS does not generate neither XML_CONT_CONS nor a REMS receipt with this Evidence		
12		After waiting the predefined period of time for receiving the REMS receipt from RREMS, generates <REMS_receipt_2>_with_XML_CONT_CONS_FAIL with code RD03 and sends it back to the sender			
13	Receives <REMS_receipt_2>_with_XML_CONT_CONS_FAIL with code RD03				

5.4.3 Scenarios for Store&Forward to Store&Notify

Table 6 defines a number of scenarios for the case where SREMS operates Store and Forward and RREMS operates Store and Notify.

The scenarios are based on scenarios in Table 4 adding the relay acceptance and relay rejection events at the some of the RREMSs and their corresponding ERDS evidences.

For the sake of simplicity, it will suppose that all the entities at receiving side are served by the same RREMS. It could be possible to use the templates defined in the present document for defining scenarios where the aforementioned entities are served by different RREMSs.

Table 6: Scenarios where SREMS operates Store&Forward and RREMSs operate Store&Notify (1/5)

Scenario id: SREMS_SF_RREMS_SN#1				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {NOT_F_ACC, CONS_ACC, CONT_CONS, CONT_HAND}		First scenario for Store&Notify style, where the REMS asks to all the entities at receiving side for acceptance, and all the entities at receiving side accept. Similar scenarios to the ones present in this table could have been defined where each REMS receipt contains only one ERDS evidence, instead several. Scenario SREMS_SF_I_REMS_SF_RREMS_SF#1 in Table 8 of clause 5.5.2 is an example.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC		
4		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
5			Accepts <REM_dispatch_1>_with_XML_SUB_ACC	
6			Generates XML_REL_ACC ERDS evidence	
7			Generates <REMS_receipt_1>_with_XML_REL_ACC	
8			Sends <REMS_receipt_1>_with_XML_REL_ACC back to SREMS	
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification>_for_Acceptance	

Scenario id: SREMS_SF_RREMS_SN#1				Purpose
10			Sends <REMS_notification>_for_Acceptance to receiving side	
11			Generates XML_NOT_F_ACC ERDS evidence	All entities in receiving side answer positively
12			Generates XML_CONS_ACC ERDS evidence	
13			Generates <REM_dispatch_2>_with_XML_SUB_ ACC	
14			Sends <REM_dispatch_2>_with_XML_SUB_ ACC to receiving side	
15				<REM_dispatch_2>_ with_XML_SUB_ACC consigned to all entities in receiving side
16			Generates XML_CONT_CONS ERDS evidence	All the entities retrieve user content
17			Generates XML_CONT_HAND ERDS evidence	
18			Generates <REMS_receipt_2>_with_EV_SET#1	
19			Sends <REMS_receipt_2>_with_EV_SET#1 to SREMS	
20		Receives <REMS_receipt_2>_with_EV_SET#1		
21		Sends <REMS_receipt_2>_with_XML_XML_EV_ SET#1 back to sender		
22	Receives <REMS_receipt_2>_wit h_EV_SET#1			

Table 6a: Scenarios where SREMS operates Store&Forward and RREMSs operate Store&Notify (2/5)

Scenario id: SREMS_SF_RREMS_SN#2		Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC	Var EV_SET#1 = { NOT_F_ACC, CONS_ACC, CONS_REJ, CONT_CONS, CONT_HAND }	As scenario SREMS_SF_RREMS_SN#1 but one of the entities at the receiving side does not accept consignment.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC		
Parameter: <REMS_receipt_1>_with_XML_REL_ACC		
Parameter: <REMS_notification>_for_Acceptance		
Parameter: <REMS_receipt_2>_with_EV_SET#1		

Scenario id: SREMS_SF_RREMS_SN#2					Purpose
Sequence of actions					
#	Sender	SREMS	RREMS	Receiving side	
1	Sender sends original message				
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS			
5			Accepts <REM_dispatch_1>_with_XML_SUB_ACC		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends <REMS_receipt_1>_with_XML_REL_ACC back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification>_for_Acceptance		
10			Sends <REMS_notification>_for_Acceptance to receiving side		
11			Generates XML_NOT_F_ACC ERDS evidence for all N entities	N-1 entities in receiving side answer positively. One answers negatively	
12			Generates XML_CONS_ACC ERDS evidence for N-1 entities and one XML_CONS_REJ ERDS evidence for one entity		
13			Generates <REM_dispatch_2>_with_XML_SUB_ACC		
14			Sends <REM_dispatch_2>_with_XML_SUB_ACC to N-1 accepting entities at receiving side		
15				<REM_dispatch_2>_with_XML_SUB_ACC	

Scenario id: SREMS_SF_RREMS_SN#2				Purpose
				consigned to N-1 entities in receiving side
16			Generates one XML_CONT_CONS ERDS evidence for N-1 entities	N-1 entities retrieve user content
17			Generates one XML_CONT_HAND ERDS evidence for N-1 entities	
18			Generates <REMS_receipt_2>_with_EV_SET#1	
19			Sends <REMS_receipt_2>_with_EV_SET#1 to SREMS	
20		Receives <REMS_receipt_2>_with_EV_SET#1		
21		Sends <REMS_receipt_2>_with_XML_XML_EV_SET#1 back to sender		
22	Receives <REMS_receipt_2>_with_EV_SET#1			

Table 6b: Scenarios where SREMS operates Store&Forward and RREMSs operate Store&Notify (3/5)

Scenario id: SREMS_SF_RREMS_SN#3				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = { NOT_F_ACC, CONS_ACC, ACC_REJ_EXP, CONT_CONS, CONT_HAND }		As scenario SREMS_SF_RREMS_SN#1 but one of the entities at the receiving side does not answer in time.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC		
4		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
5			Accepts <REM_dispatch_1>_with_XML_SUB_ACC	
6			Generates XML_REL_ACC ERDS evidence	
7			Generates <REMS_receipt_1>_with_XML_REL_ACC	
8			Sends <REMS_receipt_1>_with_XML_REL_ACC back to SREMS	
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification>_for_Acceptance	
10			Sends <REMS_notification>_for_Acceptance to receiving side	
11			Generates one XML_NOT_F_ACC ERDS evidence for all N entities	N-1 entities in receiving side answer positively. One does not answer in time
12			Generates one XML_CONS_ACC ERDS evidence for N-1 entities and one XML_ACC_REJ_EXP ERDS evidence for one entity	

Scenario id: SREMS_SF_RREMS_SN#3				Purpose
13			Generates <REM_dispatch_2>_with_XML_SUB_ACC	
14			Sends <REM_dispatch_2>_with_XML_SUB_ACC to N-1 accepting entities at receiving side	
23				<REM_dispatch_2>_with_XML_SUB_ACC consigned to N-1 entities in receiving side
15			Generates one XML_CONT_CONS ERDS evidence for N-1 entities	N-1 entities retrieve user content
16			Generates one XML_CONT_HAND ERDS evidence for N-1 entities	
17			Generates <REMS_receipt_2>_with_EV_SET#1	
18			Sends <REMS_receipt_2>_with_EV_SET#1 to SREMS	
19		Receives <REMS_receipt_2>_with_EV_SET#1		
20		Sends <REMS_receipt_2>_with_XML_XML_EV_SET#1 back to sender		
21	Receives <REMS_receipt_2>_with_EV_SET#1			

Table 6c: Scenarios where SREMS operates Store&Forward and RREMSs operate Store&Notify (4/5)

Scenario id: SREMS_SF_RREMS_SN#4				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = { NOT_F_ACC, CONS_ACC, CONT_CONS, CONT_CONS_FAIL, CONT_HAND }		As first scenario in the present table, but one of the consignments fails.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		

Scenario id: SREMS_SF_RREMS_SN#4				Purpose
3		Generates <REM_dispatch_1>_with_XML_SUB_A CC		
4		Relays <REM_dispatch_1>_with_XML_SUB_A CC to RREMS		
5			Accepts <REM_dispatch_1>_with_XML_SUB_ ACC	
6			Generates XML_REL_ACC ERDS evidence	
7			Generates <REMS_receipt_1>_with_XML_REL_ ACC	
8			Sends <REMS_receipt_1>_with_XML_REL_ ACC back to SREMS	
9		Receives <REMS_receipt_1>_with_XML_REL_AC C	Generates <REMS_notification>_for_Acceptance	
10			Sends <REMS_notification>_for_Acceptance to receiving side	
11			Generates one XML_NOT_F_ACC ERDS evidence for all N entities	All the entities in receiving side answer positively
12			Generates one XML_CONS_ACC ERDS evidence for all the N entities in receiving side	
13			Generates <REM_dispatch_2>_with_XML_SUB_ ACC	
14			Successfully consigns <REM_dispatch_2>_with_XML_SUB_ ACC to N-1 entities at receiving side, one consignment fails	
15				<REM_dispatch_2>_ with_XML_SUB_ACC consigned to N-1 entities in receiving side. One consignment fails
16			Generates one XML_CONT_CONS ERDS evidence for N-1 entities and one XML_CONT_CONS_FAIL for one entity	N-1 entities retrieve user content
17			Generates one XML_CONT_HAND ERDS evidence for N-1 entities	

Scenario id: SREMS_SF_RREMS_SN#4				Purpose
18			Generates <REMS_receipt_2>_with_EV_SET#1	
19			Sends <REMS_receipt_2>_with_EV_SET#1 to SREMS	
20		Receives <REMS_receipt_2>_with_EV_SET#1		
21		Sends <REMS_receipt_2>_with_XML_XML_EV_SET#1 back to sender		
22	Receives <REMS_receipt_2>_with_EV_SET#1			

Table 6d: Scenarios where SREMS operates Store&Forward and RREMSs operate Store&Notify (5/5)

Scenario id: SREMS_SF_RREMS_SN#5				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {NOT_F_ACC, CONS_ACC, CONT_CONS, CONT_HAND, CONT_HAND_FAIL}		As first scenario in the present table, but one of the handovers fails.
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC		
4		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
5			Accepts <REM_dispatch_1>_with_XML_SUB_ACC	
6			Generates XML_REL_ACC ERDS evidence	
7			Generates <REMS_receipt_1>_with_XML_REL_ACC	

Scenario id: SREMS_SF_RREMS_SN#5				Purpose
8			Sends <REM_receipt_1>_with_XML_XML_REL_ACC back to SREMS	
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification>_for_Acceptance	
10			Sends <REMS_notification>_for_Acceptance to receiving side	
11			Generates one XML_NOT_F_ACC ERDS evidence for all the N entities	All the entities in receiving side answer positively.
12			Generates one XML_CONS_ACC ERDS evidence for all the N entities in receiving side	
13			Generates <REM_dispatch_2>_with_XML_SUB_ACC	
14			Sends <REM_dispatch_2>_with_XML_SUB_ACC to all entities at receiving side	
15				<REM_dispatch_2>_with_XML_SUB_ACC consigned to receiving side
16			Generates one XML_CONT_CONS ERDS evidence for all the N entities	N-1 entities retrieve user content. One fails
17			Generates one XML_CONT_HAND ERDS evidence for N-1 entities and one XML_CONT_HAND_FAIL for one entity	
18			Generates <REMS_receipt_2>_with_EV_SET#1	
19			Sends <REMS_receipt_2>_with_EV_SET#1 to SREMS	
20		Receives <REMS_receipt_2>_with_EV_SET#1		
21		Sends <REMS_receipt_2>_with_XML_XML_EV_SET#1 back to sender		
22	Receives <REMS_receipt_2>_with_EV_SET#1			

5.4.4 Scenarios for Store&Notify to Store&Forward

Table 7 defines a number of scenarios for the case where SREMS operates Store and Notify and RREMS operates Store and Forward.

For the sake of simplicity, it will suppose that all the entities at receiving side are served by the same RREMS. It could be possible to use the templates defined in the present document for defining scenarios where the aforementioned entities are served by different RREMSs.

Table 7: Scenarios where SREMS operates Store&Notify and RREMSs operate Store&Forward (1/5)

Scenario id: SREMS SN RREMS SF#1				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_CONT_CONS, XML_CONT_HAND }		Successful scenario where the REM dispatch is successfully consigned to all the entities in receiving side and all the entities successfully retrieve it. This scenario is slightly different than the one shown in clause 4.3.2.3 of ETSI EN 319 532-1 [3] because it groups the two last ERDS evidence generated by RREMS in one unique REMS receipt
Parameter: <REMS_notification_1>_for_Acceptance				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification_2>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_XML_NOT_F_ACC				
Parameter: <REMS_receipt_3>_with_XML_CONS_ACC				
Parameter: <REMS_receipt_4>_with_XML_REL_ACC				
Parameter: <REMS_receipt_5>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC and stores it internally Generates <REMS_notification_1>_for_Acceptance		
4		Relays <REMS_notification_1>_for_Acceptance		
5			Accepts <REMS_notification_1>_for_Acceptance	
6			Generates XML_REL_ACC ERDS evidence	
7			Generates <REMS_receipt_1>_with_XML_REL_ACC	
			Sends <REMS_receipt_1>_with_XML_REL_ACC back to SREMS	
8		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_2>_for_Acceptance	
9			Sends <REMS_notification_2>_for_Acceptance to receiving side	
10			Generates XML_NOT_F_ACC ERDS evidence	
11			Generates <REMS_receipt_2>_with_XML_NOT_F_ACC	

Scenario id: SREMS_SN_RREMS_SF#1				Purpose
12			Sends <REMS_receipt_2>_with_XML_NOT_F_ACC back to SREMS	
13		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC		
14				All the entities at receiving side answer positively to SREMS
15		Generates XML_CONS_ACC ERDS evidence for all entities at receiving side		
16		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
17		Generates <REMS_receipt_3>_with_XML_CONS_ACC	Receives <REM_dispatch_1>_with_XML_SUB_ACC	
18		Sends it to sender	Generates XML_REL_ACC ERDS evidence	
19	Receives <REMS_receipt_3>_with_XML_CONS_ACC		Generates <REMS_receipt_3>_with_XML_REL_ACC	
20			Sends it back to SREMS	
21		Receives <REMS_receipt_4>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC	
22			Consigns it to receiving side	
23			Generates XML_CONT_CONS ERDS evidence for all entities at receiving side	All the entities at receiving side retrieve the user content
24			Generates XML_CONT_HAND ERDS evidence for all entities at receiving side	
25			Generates <REMS_receipt_5>_with_EV_SET#1	
26			Sends <REMS_receipt_5>_with_EV_SET#1 to SREMS	
27		Receives <REMS_receipt_5>_with_EV_SET#1		
28		Sends <REMS_receipt_5>_with_EV_SET#1 back to sender		

Scenario id: SREMS_SN_RREMS_SF#1				Purpose
29	Receives <REMS_receipt_5>_with_ EV_SET#1			

Table 7a: Scenarios where SREMS operates Store&Notify and RREMSs operate Store&Forward (2/5)

Scenario id: SREMS_SN_RREMS_SF#2				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = { CONS_ACC, CONS_REJ }		As scenario SREMS_SN_RREMS_SF#1 but now one of the entities at receiving side rejects the consignment.
Parameter: <REMS_notification_1>_for_Acceptance		Var EV_SET#2 = {CONT_CONS, CONT_HAND}		
Parameter: <REMS_notification_2>_for_Acceptance				
Parameter: <REMS_receipt_1>_with_XML_NOT_F_ACC				
Parameter: <REMS_receipt_2>_with_XML_EV_SET#1				
Parameter: <REMS_receipt_3>_with_XML_XML_REL_ACC				
Parameter: <REMS_receipt_4>_with_EV_SET#2				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC and stores it internally		
4		Relays <REMS_notification_1>_for_Acceptance		
5		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_2>_for_Acceptance	
6			Sends <REMS_notification_2>_for_Acceptance to receiving side	
7			Generates XML_NOT_F_ACC ERDS evidence	
8			Generates <REMS_receipt_1>_with_XML_NOT_F_ACC	
9			Sends <REMS_receipt_1>_with_XML_NOT_F_ACC back to SREMS	
10		Receives <REMS_receipt_1>_with_XML_NOT_F_ACC		

Scenario id: SREMS_SN_RREMS_SF#2					Purpose
11				N-1 entities at receiving side answer positively to SREMS. One answers negatively to SREMS.	
12		Generates one XML_CONS_ACC ERDS evidence for N-1 accepting entities, generates one XML_CONS_REJ evidence for the one rejecting entity.			
13		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS for N-1 accepting entities			
14		Generates <REMS_receipt_2>_with_XML_EV_SET #1	Receives <REM_dispatch_1>_with_XML_SUB_ACC		
15		Sends <REMS_receipt_2>_with_XML_EV_SET #1 back to sender	Generates XML_REL_ACC ERDS evidence		
16	Receives <REMS_receipt_2>_with_XML_EV_SET#1		Generates <REMS_receipt_3>_with_XML_REL_ACC		
17			Sends it back to SREMS		
18		Receives <REMS_receipt_3>_with_XML_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
19			Consigns it to receiving side for N-1 accepting entities		
20			Generates one XML_CONT_CONS ERDS evidence for N-1 accepting entities	N-1 entities at receiving side retrieve the user content	
21			Generates one XML_CONT_HAND ERDS evidence for N-1 accepting entities		
22			Generates <REMS_receipt_4>_with_EV_SET#2		
23			Sends <REMS_receipt_4>_with_EV_SET#2 to SREMS		
24		Receives <REMS_receipt_4>_with_EV_SET#2			
25		Sends <REMS_receipt_4>_with_EV_SET#2 back to sender			
26	Receives <REMS_receipt_4>_with_EV_SET#2				

Table 7b: Scenarios where SREMS operates Store&Notify and RREMSs operate Store&Forward (3/5)

Scenario id: SREMS_SN_RREMS_SF#3				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		EV_SET#1 = {CONT_CONS, CONT_HAND}		As the first scenario in the present table but now one of the entities at receiving side does not answer in time to the notification for acceptance of SREMS.
Parameter: <REMS_notification_1>_for_Acceptance				
Parameter: <REMS_notification_2>_for_Acceptance				
Parameter: <REMS_receipt_1>_with_XML_NOT_F_ACC				
Parameter: <REMS_receipt_2>_with_XML_CONS_ACC				
Parameter: <REMS_receipt_3>_with_XML_XML_REL_ACC				
Parameter: <REMS_receipt_4>_with_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC and stores it internally		
4		Relays <REMS_notification_1>_for_Acceptance		
5			Accepts <REMS_notification_1>_for_Acceptance	
6		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_2>_for_Acceptance	
7			Sends <REMS_notification_2>_for_Acceptance to receiving side	
8			Generates XML_NOT_F_ACC ERDS evidence	
9			Generates <REMS_receipt_1>_with_XML_NOT_F_ACC	
10			Sends <REMS_receipt_1>_with_XML_NOT_F_ACC back to SREMS	
11		Receives <REMS_receipt_1>_with_XML_NOT_F_ACC		

Scenario id: SREMS_SN_RREMS_SF#3					Purpose
12				N-1 entities at receiving side answer positively to SREMS. One does not answer in time to SREMS	
13		Generates XML_CONS_ACC ERDS evidence for N-1 accepting entities, generates XML_ACC_REJ_EXP ERDS evidence for the one entity which did not respond in time.			
14		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS for N-1 accepting entities			
15		Generates <REMS_receipt_2>_with_XML_CONS_ACC	Receives <REM_dispatch_1>_with_XML_SUB_ACC		
16		Sends <REMS_receipt_2>_with_XML_CONS_ACC back to sender	Generates XML_REL_ACC ERDS evidence		
17	Receives <REMS_receipt_2>_with_XML_CONS_ACC		Generates <REMS_receipt_3>_with_XML_REL_ACC		
18			Sends it back to SREMS		
19		Receives <REMS_receipt_3>_with_XML_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
20			Consigns it to receiving side for N-1 accepting entities		
21			Generates XML_CONT_CONS ERDS evidence for N-1 accepting entities	N-1 entities at receiving side retrieve the user content	
22			Generates XML_CONT_HAND ERDS evidence for N-1 accepting entities		
23			Generates <REMS_receipt_4>_with_EV_SET#1		
24			Sends <REMS_receipt_4>_with_EV_SET#1 to SREMS		
25		Receives <REMS_receipt_4>_with_EV_SET#1			
26		Sends <REMS_receipt_4>_with_EV_SET#1 back to sender			
27	Receives <REMS_receipt_>_with_EV_SET#21				

Table 7c: Scenarios where SREMS operates Store&Notify and RREMSs operate Store&Forward (4/5)

Scenario id: SREMS_SN_RREMS_SF#4				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {CONT_CONS, CONT_CONS_FAIL }		As the first scenario in the present table but now one of the consignments to the receiving side fails.
Parameter: <REMS_notification_1>_for_Acceptance				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification_2>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_XML_NOT_F_ACC				
Parameter: <REMS_receipt_3>_with_XML_CONS_ACC				
Parameter: <REMS_receipt_4>_with_XML_REL_ACC				
Parameter: <REMS_receipt_5>_EV_SET#1				
Parameter: <REMS_receipt_6>_XML_CONT_HAND				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC and stores it internally		
4		Relays <REMS_notification_1>_for_Acceptance		
5			Accepts <REMS_notification_1>_for_Acceptance	
6			Generates <REMS_notification_2>_for_Acceptance	
7			Sends <REMS_notification_2>_for_Acceptance to receiving side	
8			Generates XML_NOT_F_ACC ERDS evidence	
9			Generates <REMS_receipt_2>_with_XML_NOT_F_ACC	
10			Sends <REMS_receipt_2>_with_XML_NOT_F_ACC back to SREMS	
11		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC		
12				All the entities at receiving side answer positively to SREMS

Scenario id: SREMS_SN_RREMS_SF#4				Purpose
13		Generates XML_CONS_ACC ERDS evidence for all entities at receiving side		
14		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
15		Generates <REMS_receipt_3>_with_XML_CONS_ACC	Receives <REM_dispatch_1>_with_XML_SUB_ACC	
16		Sends <REMS_receipt_3>_with_XML_CONS_ACC back to sender	Generates XML_REL_ACC ERDS evidence	
17	Receives <REMS_receipt_3>_with_XML_CONS_ACC		Generates <REMS_receipt_4>_with_XML_REL_ACC ERDS evidence	
18			Sends it back to SREMS	
19		Receives <REMS_receipt_4>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC	
20			Consigns it to receiving side	
21				N-1 consignments succeed, one fails
22			Generates XML_CONT_CONS for N-1 entities and one XML_CONS_FAIL for one entity	
23			Generates <REMS_receipt_5>_with_EV_SET#1	
24			Sends <REMS_receipt_5>_with_EV_SET#1 back to SREMS	
25		Receives <REMS_receipt_4>_with_EV_SET#1		
26				
27				N-1 entities at receiving side retrieve the user content
28			Generates XML_CONT_HAND ERDS evidence for N-1 entities	
29			Generates <REMS_receipt_5>_with_XML_CONT_HAND	
30			Sends <REMS_receipt_5>_with_XML_CONT_HAND to SREMS	

Scenario id: SREMS_SN_RREMS_SF#4				Purpose
31		Receives <REMS_receipt_5>_with_XML_CONT_HAND		
32		Sends <REMS_receipt_5>_with_XML_CONT_HAND back to sender		
33	Receives <REMS_receipt_5>_with_XML_CONT_HAND			

Table 7d: Scenarios where SREMS operates Store&Notify and RREMSs operate Store&Forward (5/5)

Scenario id: SREMS_SN_RREMS_SF#5				Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {CONT_CONS, CONT_HAND, CONT_HAND_FAIL }		As the first scenario in the present table but now one of the handovers to the receiving side fails.
Parameter: <REMS_notification_1>_for_Acceptance				
Parameter: <REMS_receipt_1>_with_XML_REL_ACC				
Parameter: <REMS_notification_2>_for_Acceptance				
Parameter: <REMS_receipt_2>_with_XML_NOT_F_ACC				
Parameter: <REMS_receipt_3>_with_XML_CONS_ACC				
Parameter: <REMS_receipt_4>_with_XML_REL_ACC				
Parameter: <REMS_receipt_5>_EV_SET#1				
Sequence of actions				
#	Sender	SREMS	RREMS	Receiving side
1	Sender sends original message			
2		Accepts submission. Generates XML_SUB_ACC ERDS evidence		
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC and stores it internally		
4		Relays <REMS_notification_1>_for_Acceptance		
5			Accepts <REMS_notification_1>_for_Acceptance	
6			Generates <REMS_notification_2>_for_Acceptance	
7			Sends <REMS_notification_2>_for_Acceptance to receiving side	
8			Generates XML_NOT_F_ACC ERDS evidence	

Scenario id: SREMS_SN_RREMS_SF#5				Purpose
9			Generates <REMS_receipt_2>_with_XML_NOT_F_ACC	
10			Sends <REMS_receipt_2>_with_XML_NOT_F_ACC back to SREMS	
11		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC		
12				All the entities at receiving side answer positively to SREMS.
13		Generates XML_CONS_ACC ERDS evidence for all entities at receiving side		
14		Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
15		Generates <REMS_receipt_3>_with_XML_CONS_ACC ERDS evidence	Receives <REM_dispatch_1>_with_XML_SUB_ACC	
16		Sends <REMS_receipt_3>_with_XML_CONS_ACC to sender	Generates XML_REL_ACC ERDS evidence	
17	Receives <REMS_receipt_3>_with_XML_CONS_ACC		Generates <REMS_receipt_4>_with_XML_REL_ACC ERDS evidence	
18			Sends it back to SREMS	
19		Receives <REMS_receipt_4>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC	
20			Consigns it to receiving side	
21			Generates XML_CONT_CONS ERDS evidence for all entities at receiving side	N-1 entities at receiving side retrieve the user content. One entity fails when trying to retrieve.
22			Generates XML_CONT_HAND ERDS evidence for N-1 entities and XML_CONT_HAND_FAIL for one entity	
23			Generates <REMS_receipt_5>_with_EV_SET#1	
24			Sends <REMS_receipt_5>_with_EV_SET#1 to SREMS	
25		Receives <REMS_receipt_5>_with_EV_SET#1		

Scenario id: SREMS_SN_RREMS_SF#5				Purpose
26		Sends <REMS_receipt_5>_with_EV_SET#1 back to sender		
27	Receives <REMS_receipt_5>_with_ EV_SET#1			

5.5 Scenarios for extended model

5.5.1 Introduction

The present clause defines test cases for scenarios that take place when the sender and the entities at the receiving side are subscribed to different REMSs and there is one intermediate IREMS between the SREMS and the RREMSs.

Clause 5.5.2 defines test cases when the all the REMSs operate in Store and Forward style.

Clause 5.5.3 defines test cases when the SREMS and the RREMS operate in Store and Forward style and the IREMS operates in Store and Notify style.

5.5.2 Scenarios for S&F->S&F->S&F

Table 8 shows scenarios where SREMS, IREMS and RREMS all operate in Store and Forward style.

The sets of scenarios shown in Table 8 extend the set shown in clause 4.4.2.1 of ETSI EN 319 532-1 [3].

Table 8: Scenarios where SREMS, IREMS, RREMSs all operate in Store&Forward style (1/5)

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#1					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC					First scenario where the N entities successfully retrieve the REM dispatch with the user content.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC					
Parameter: <REMS_receipt_2>_with_XML_REL_ACC					
Parameter: <REMS_receipt_3>_with_XML_CONT_CONS					
Parameter: <REMS_receipt_4>_with_XML_CONT_HAND					
Sequence of actions					
#	Sender	SREMS	IREMS	RREMS	Receiving side
1	Sender sends original message				
2		Accepts submission and generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to IREMS			
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends it back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
10				Receives <REM_dispatch_1>_with_XML_SUB_ACC	
11				Generates XML_REL_ACC ERDS evidence	
12				Generates <REMS_receipt_2>_with_XML_REL_ACC	
13				Sends it back to IREMS	
14			Receives <REMS_receipt_2>_with_XML_REL_ACC	Consigns <REM_dispatch_1>_with_XML_SUB_ACC to receiving side	

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#1					Purpose
15					<REM_dispatch_1>_with_XML_SUB_ACC consigned to all the entities in receiving side
16				Generates XML_CONT_CONS ERDS evidence	
17				Generates <REMS_receipt_3>_with_XML_CONT_CONS	All the entities in receiving side retrieve <REM_dispatch_1>_with_XML_SUB_ACC
18				Sends it back to IREMS	
19			Receives <REMS_receipt_3>_with_XML_CONT_CONS	Generates XML_CONT_HAND ERDS evidence	
20			Sends it back to SREMS	Generates <REMS_receipt_4>_with_XML_CONT_HAND	
21		Receives <REMS_receipt_3>_with_XML_CONT_CONS		Sends it back to IREMS	
22		Sends it back to sender	Receives <REMS_receipt_4>_with_XML_CONT_HAND		
23	Receives <REMS_receipt_3>_with_XML_CONT_CONS		Sends it back to SREMS		
24		Receives <REMS_receipt_4>_with_XML_CONT_HAND			
25		Sends it back to sender			
26	Receives <REMS_receipt_4>_with_XML_CONT_HAND				

Table 8a: Scenarios where SREMS, IREMS, RREMSs all operate in Store&Forward style (2/5)

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#2					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC			Var EV_SET#1 = {CONT_CONS, CONT_CONS_FAIL}		As the first scenario but now one of the consignments fails.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC					
Parameter: <REMS_receipt_2>_with_XML_REL_ACC					
Parameter: <REMS_receipt_3>_with_EV_SET#1					
Parameter: <REMS_receipt_4>_with_XML_CONT_HAND					
Sequence of actions					
#	Sender	SREMS	IREMS	RREMS	Receiving side
1	Sender sends original message				
2		Accepts submission and generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to IREMS			
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends it back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
10				Receives <REM_dispatch_1>_with_XML_SUB_ACC	
11				Generates XML_REL_ACC ERDS evidence	
12				Generates <REMS_receipt_2>_with_XML_REL_ACC	
13				Sends it back to IREMS	
14			Receives <REMS_receipt_2>_with_XML_REL_ACC	Consigns <REM_dispatch_1>_with_XML_SUB_ACC to the receiving side	

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#2					Purpose
15					<REM_dispatch_2>_with_XML_SUB_ACC is consigned to N-1 entities in receiving side. One of the consignments fails
16				Generates XML_CONT_CONSERDS evidence for N-1 entities and XML_CONT_CONS_FAILERDS evidence for one entity	
17				Generates <REMS_receipt_3>_with_EV_SET#1	N-1 entities in receiving side retrieve <REM_dispatch_2>_with_XML_SUB_ACC
18				Sends it back to IREMS	
19			Receives <REMS_receipt_3>_with_EV_SET#1	Generates XML_CONT_HAND for N-1 entities	
20			Sends it back to SREMS	Generates <REMS_receipt_4>_with_XML_CONT_HAND	
21		Receives <REMS_receipt_3>_with_EV_SET#1		Sends it back to IREMS	
22		Sends it back to sender	Receives <REMS_receipt_4>_with_XML_CONT_HAND		
23	Receives <REMS_receipt_3>_with_EV_SET#1		Sends it back to SREMS		
24		Receives <REMS_receipt_4>_with_XML_CONT_HAND			
25		Sends it back to sender			
26	Receives <REMS_receipt_4>_with_XML_CONT_HAND				

Table 8b: Scenarios where SREMS, IREMS, RREMSs all operate in Store&Forward style (3/5)

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#3					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC			Var EV_SET#1 = { CONT_HAND, CONT_HAND_FAIL }		As the first scenario but now one of the entities fails when trying to retrieve the user content.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC					
Parameter: <REMS_receipt_2>_with_XML_REL_ACC					
Parameter: <REMS_receipt_3>_with_XML_CONT_CONS					
Parameter: <REMS_receipt_4>_with_EV_SET#1					
Sequence of actions					
#	Sender	SREMS	IREMS	RREMS	Receiving side
1	Sender sends original message				
2		Accepts submission and generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relies it to IREMS			
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends it back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Relies <REM_dispatch_1>_with_XML_SUB_ACC to RREMS		
10				Receives <REM_dispatch_1>_with_XML_SUB_ACC to RREMS	
11				Generates XML_REL_ACC ERDS evidence	
12				Generates <REMS_receipt_2>_with_XML_SUB_ACC	
13				Sends it back to IREMS	
14			Receives <REMS_receipt_2>_with_XML_SUB_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC to RREMS	
15				Consigns it to receiving side	

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#3						Purpose
16					<REM_dispatch_2>_with_XML_SUB_ACC to RREMS is consigned all the entities	
17				Generates XML_CONT_CONS ERDS evidence		
18				Generates <REMS_receipt_3>_with_XML_XML_CONT_CONS	N-1 entities in receiving side retrieve <REM_dispatch_2>_with_XML_SUB_ACC to RREMS. One entity fails when trying to retrieve it	
19				Sends it back to IREMS		
20			Receives <REMS_receipt_3>_with_XML_XML_CONT_CONS	Generates XML_CONT_HAND ERDS evidence for N-1 entities and XML_CONT_HAND_FAIL for one entity		
21			Sends it back to SREMS	Generates <REMS_receipt_4>_with_EV_SET#1		
22		Receives <REMS_receipt_3>_with_XML_XML_CONT_CONS		Sends it back to IREMS		
23		Sends it back to sender	Receives <REMS_receipt_4>_with_EV_SET#1			
24	Receives <REMS_receipt_3>_with_XML_XML_CONT_CONS		Sends it back to SREMS			
25		Receives <REMS_receipt_4>_with_EV_SET#1				
26		Sends it back to sender				
27	Receives <REMS_receipt_4>_with_EV_SET#1					

Table 8c: Scenarios where SREMS, IREMS, RREMSs all operate in Store&Forward style (4/5)

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#4						Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC						As the first scenario but now the IREMS rejects relaying.
Parameter: <REMS_receipt_1>_with_XML_REL_REJ						
Sequence of actions						
#	Sender	SREMS	IREMS	RREMS	Receiving side	
1	Sender sends original message					
2		Accepts submission and generates XML_SUB_ACC ERDS evidence				
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC				
4		Relays it to IREMS				
5			Rejects relay			
6			Generates XML_REL_REJ ERDS evidence			
7			Generates <REMS_receipt_1>_with_XML_REL_REJ			
8			Sends it back to SREMS			
9		Receives <REMS_receipt_1>_with_XML_REL_REJ				
10		Sends it back to sender				
11	Receives <REMS_receipt_1>_with_XML_REL_REJ					

Table 8d: Scenarios where SREMS, IREMS, RREMSs all operate in Store&Forward style (5/5)

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#5						Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC						As the first scenario but now the RREMS rejects relaying.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC						
Parameter: <REMS_receipt_2>_with_XML_REL_REJ						
Sequence of actions						
#	Sender	SREMS	IREMS	RREMS	Receiving side	
1	Sender sends original message					
2		Accepts submission and generates XML_SUB_ACC ERDS evidence				

Scenario id: SREMS_SF_IREMS_SF_RREMS_SF#5						Purpose
3		Generates <REM_dispatch_1>_with_X ML_SUB_ACC				
4		Relays it to IREMS				
5			Receives <REM_dispatch_1>_with_XM L_SUB_ACC			
6			Generates XML_REL_ACC ERDS evidence			
7			Generates <REMS_receipt_1>_with_XM L_REL_ACC			
8			Sends it back to SREMS			
9		Receives <REMS_receipt_1>_with_X ML_REL_ACC	Relays <REM_dispatch_1>_with_XM L_SUB_ACC to RREMS			
10				Receives <REM_dispatch_1>_with_XML SUB_ACC but it rejects it		
11				Generates XML_REL_REJ ERDS evidence		
12				Generates <REMS_receipt_2>_with_XML REL_REJ		
13				Sends it back to IREMS		
14			Receives <REMS_receipt_2>_with_XM L_REL_REJ			
15			Sends it back to SREMS			
16		Receives <REMS_receipt_2>_with_X ML_REL_REJ				
17		Sends it back to sender				
18	Receives <REMS_receipt_2>_wi th_XML_REL_REJ					

5.5.3 Scenarios for S&F -> S&N -> S&F

Table 9 shows scenarios where SREMS, and RREMS operate Store and Forward style and IREMS operates Store and Notify.

The sets of scenarios shown in Table 9 extend the set shown in clause 4.4.2.2 of ETSI EN 319 532-1 [3].

Table 9: Scenarios where SREMS and RREMSs operate Store&Forward style and IREMS operates Store&Notify (1/3)

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#1						Purpose
Parameter: <REM_dispatch_1> with XML_SUB_ACC						First scenario where all the entities at receiving side successfully retrieve the user content.
Parameter: <REMS_receipt_1> with XML_REL_ACC						
Parameter: <REMS_notification_1>_for_Acceptance						
Parameter: <REMS_receipt_2> with XML_NOT_F_ACC						
Parameter: <REMS_receipt_3> with XML_CONS_ACC						
Parameter: <REMS_receipt_4> with XML_REL_ACC						
Parameter: <REM_dispatch_2> with XML_SUB_ACC						
Parameter: <REMS_receipt_5> with XML_CONT_CONS						
Parameter: <REMS_receipt_6> with XML_CONT_HAND						
Sequence of actions						
#	Sender	SREMS	IREMS	RREMS	Receiving side	
1	Sender sends original message					
2		Accepts submission and generates XML_SUB_ACC ERDS evidence				
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC				
4		Relays it to IREMS				
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC and stores it			
6			Generates XML_REL_ACC ERDS evidence			
7			Generates <REMS_receipt_1>_with_XML_REL_ACC			
8			Sends it back to SREMS			
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_1>_for_Acceptance			
10			Relays <REMS_notification_1>_for_Acceptance to RREMS			
11				Receives <REMS_notification_1>_for_Acceptance		
12				Sends <REMS_notification_1>_for_Acceptance to receiving side		

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#1					Purpose	
13				Generates XML_NOT_F_ACC ERDS evidence	All the parties at receiving side receive <REMS_notification_1>_for_Acceptance	
14				Generates <REMS_receipt_2>_with_XML_NOT_F_ACC		
15				Sends it back to IREMS		
16			Receives <REMS_receipt_2>_with_XML_NOT_F_ACC			
17			Sends it back to SREMS			
18		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC				
19						All the parties at receiving side access IREMS and accept consignment
20			Generates XML_CONS_ACC for all the N entities at receiving side			
21			Generates <REMS_receipt_3>_with_XML_CONS_ACC			
22			Sends it back to SREMS			
23		Receives <REMS_receipt_3>_with_XML_CONS_ACC	Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS			
24				Accepts <REM_dispatch_1>_with_XML_SUB_ACC		
25				Generates XML_REL_ACC ERDS evidence		
26				Generates <REMS_receipt_4>_with_XML_REL_ACC		
27				Sends it back to IREMS		
28			Receives <REMS_receipt_4>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
29				Consigns <REM_dispatch_2>_with_XML_SUB_ACC to receiving side		

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#1					Purpose
30					<REM_dispatch_2>_with_XML_REL_ACC is consigned to all entities in receiving side
31				Generates XML_CONT_CONS ERDS evidence	
32				Generates <REMS_receipt_5>_with_XML_CONT_CONS	
33				Sends it back to IREMS	All entities in receiving side retrieve user content
34			Receives <REMS_receipt_5>_with_XML_CONT_CONS	Generates XML_CONT_CONT_HAND evidence	
35			sends it back to SREMS	Generates <REMS_receipt_6>_with_XML_CONT_HAND	
36		Receives <REMS_receipt_5>_with_XML_CONT_CONS		Sends it back to IREMS	
37		Sends it back to sender	Receives <REMS_receipt_6>_with_XML_CONT_HAND		
38	Receives <REMS_receipt_5>_with_XML_CONT_CONS		sends it back to SREMS		
39		Receives <REMS_receipt_6>_with_XML_CONT_HAND			
40		Sends it back to sender			
41	Receives <REMS_receipt_6>_with_XML_CONT_HAND				

Table 9a: Scenarios where SREMS and RREMSs operate Store&Forward style and IREMS operates Store&Notify (2/3)

Scenario id: SREMS_SF IREMS_SN RREMS_SF#2					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_CONS_ACC, XML_CONS_REJ}			As first scenario but now one of the entities at receiving side rejects consignment.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC					
Parameter: <REMS_notification_1>_for_Acceptance					
Parameter: <REMS_receipt_2>_with_XML_NOT_F_ACC					
Parameter: <REMS_receipt_3>_with_EV_SET#1					
Parameter: <REMS_receipt_4>_with_XML_REL_ACC					
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_5>_with_XML_CONT_CONS					
Parameter: <REMS_receipt_6>_with_XML_CONT_HAND					
Sequence of actions					
#	Sender	SREMS	IREMS	RREMS	Receiving side
1	Sender sends original message				
2		Accepts submission and generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to IREMS			
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC and stores it		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends it back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_1>_for_Acceptance		
10			Relays <REMS_notification_1>_for_Acceptance to RREMS		
11				Receives <REMS_notification_1>_for_Acceptance	
12				Sends <REMS_notification_1>_for_Acceptance to receiving side	

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#2						Purpose
13				Generates XML_NOT_F_ACC ERDS evidence	All the parties at receiving side receive <REMS_notification_1>_for_Acceptance	
14				Generates <REMS_receipt_2>_with_XML_NOT_F_ACC	.	
15				Sends it back to IREMS		
16			Receives <REMS_receipt_2>_with_XML_NOT_F_ACC			
17			Sends it back to SREMS		N-1 parties at receiving side access IREMS and accept consignment. One party rejects it	
18		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC	Generates XML_CONS_ACC ERDS evidence for N-1 entities at receiving side and one XML_CONS_REJ ERDS evidence for one entity at receiving side.			
19			Generates <REMS_receipt_3>_with_EV_SET#1			
20			Sends it back to SREMS			
21		Receives <REMS_receipt_3>_with_EV_SET#1	Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS for the N-1 accepting entities			
22		Sends it back to sender		Accepts <REM_dispatch_1>_with_XML_SUB_ACC		
23	Receives <REMS_receipt_3>_with_EV_SET#1			Generates XML_REL_ACC ERDS evidence		
24				Generates <REMS_receipt_4>_with_XML_REL_ACC		
25				Sends it back to IREMS		
26			Receives <REMS_receipt_4>_with_XML_REL_ACC	Generates <REM_dispatch_2>_with_XML_SUB_ACC		
27				Consigns <REM_dispatch_2>_with_XML_SUB_ACC to N-1 accepting entities at receiving side		

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#2					Purpose
28					<REM_dispatch_2>_with_XML_SUB_ACC is consigned to N-1 entities at receiving side
29				Generates XML_CONT_CONS ERDS evidence for N-1 entities	
30				Generates <REMS_receipt_5>_with_XML_CONT_CONS	
31				Sends it back to IREMS	N-1 entities in receiving side retrieve user content
32			Receives <REMS_receipt_5>_with_XML_CONT_CONS	Generates XML_CONT_HAND evidence for N-1 entities	
33			sends it back to SREMS	Generates <REMS_receipt_6>_with_XML_CONT_HAND	
34		Receives <REMS_receipt_5>_with_XML_CONT_CONS		Sends it back to IREMS	
35		Sends it back to sender	Receives <REMS_receipt_6>_with_XML_CONT_HAND		
36	Receives <REMS_receipt_5>_with_XML_CONT_CONS		sends it back to SREMS		
37		Receives <REMS_receipt_6>_with_XML_CONT_HAND			
38		Sends it back to sender			
39	Receives <REMS_receipt_6>_with_XML_CONT_HAND				

Table 9b: Scenarios where SREMS and RREMSs operate Store&Forward style and IREMS operates Store&Notify (3/3)

Scenario id: SREMS_SF IREMS_SN RREMS_SF#3					Purpose
Parameter: <REM_dispatch_1>_with_XML_SUB_ACC		Var EV_SET#1 = {XML_CONS_ACC, XML_CONS_REJ}			As first scenario but now one of the entities at receiving side rejects consignment and another entity fails in retrieving the user content.
Parameter: <REMS_receipt_1>_with_XML_REL_ACC		Var EV_SET#2 = {XML_CONT_HAND, XML_CONT_HAND_FAIL}			
Parameter: <REMS_notification_1>_for_Acceptance					
Parameter: <REMS_receipt_2>_with_XML_NOT_F_ACC					
Parameter: <REMS_receipt_3>_with_EV_SET#1					
Parameter: <REMS_receipt_4>_with_XML_REL_ACC					
Parameter: <REM_dispatch_2>_with_XML_SUB_ACC					
Parameter: <REMS_receipt_5>_with_XML_CONT_CONS					
Parameter: <REMS_receipt_6>_with_EV_SET#2					
Sequence of actions					
#	Sender	SREMS	IREMS	RREMS	Receiving side
1	Sender sends original message				
2		Accepts submission and generates XML_SUB_ACC ERDS evidence			
3		Generates <REM_dispatch_1>_with_XML_SUB_ACC			
4		Relays it to IREMS			
5			Receives <REM_dispatch_1>_with_XML_SUB_ACC and stores it		
6			Generates XML_REL_ACC ERDS evidence		
7			Generates <REMS_receipt_1>_with_XML_REL_ACC		
8			Sends it back to SREMS		
9		Receives <REMS_receipt_1>_with_XML_REL_ACC	Generates <REMS_notification_1>_for_Acceptance		
10			Relays <REMS_notification_1>_for_Acceptance to RREMS		
11				Receives <REMS_notification_1>_for_Acceptance	
12				Sends <REMS_notification_1>_for_Acceptance to receiving side	

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#3					Purpose
13				Generates XML_NOT_F_ACC ERDS evidence	All the parties at receiving side receive <REMS_notification_1>_for_Acceptance
14				Generates <REMS_receipt_2>_with_XML_NOT_F_ACC	
15				Sends it back to IREMS	
16			Receives <REMS_receipt_2>_with_XML_NOT_F_ACC		
17			Sends it back to SREMS		N-1 parties at receiving side access IREMS and accept consignment. One party rejects it
18		Receives <REMS_receipt_2>_with_XML_NOT_F_ACC	Generates XML_CONS_ACC ERDS evidence for N-1 entities at receiving side and one XML_CONS_REJ ERDS evidence for one entity at receiving side.		
19			Generates <REMS_receipt_3>_with_EV_SET#1		
20			Sends it back to SREMS		
21		Receives <REMS_receipt_3>_with_EV_SET#1	Relays <REM_dispatch_1>_with_XML_SUB_ACC to RREMS for the N-1 accepting entities		
22		Sends it back to sender		Accepts <REM_dispatch_1>_with_XML_SUB_ACC	
23	Receives <REMS_receipt_3>_with_EV_SET#1			Generates XML_REL_ACC ERDS evidence	
24				Generates <REMS_receipt_4>_with_XML_REL_ACC	
25				Sends it back to IREMS	
26				Generates <REM_dispatch_2>_with_XML_SUB_ACC	
27			Receives <REMS_receipt_4>_with_XML_REL_ACC	Consigns <REM_dispatch_2>_with_XML_SUB_ACC to N-1 accepting entities at receiving side	

Scenario id: SREMS_SF_IREMS_SN_RREMS_SF#3						Purpose
28					<REM_dispatch_2>_with_XML_SUB_ACC is consigned to N-1 entities at receiving side	
29				Generates XML_CONT_CONSERDS evidence for N-1 entities		
30				Generates <REMS_receipt_5>_with_XML_CONT_CONS		
31				Sends it back to IREMS	N-2 entities in receiving side retrieve user content, one entity fails	
32			Receives <REMS_receipt_5>_with_XML_CONT_CONS	Generates XML_CONT_HAND evidence for N-2 entities and XML_CONT_HAND_FAIL for one entity		
33			sends it back to SREMS	Generates <REMS_receipt_6>_with_EV_SET#2		
34		Receives <REMS_receipt_5>_with_XML_CONT_CONS		Sends it back to IREMS		
35		Sends it back to sender	Receives <REMS_receipt_6>_with_EV_SET#2			
36	Receives <REMS_receipt_5>_with_XML_CONT_CONS		sends it back to SREMS			
37		Receives <REMS_receipt_6>_with_EV_SET#2				
38		Sends it back to sender				
39	Receives <REMS_receipt_6>_with_EV_SET#2					

6 REM Messages instances

6.1 Introduction and technical approach

The present clause defines a number of instances of the different types of REM Messages, namely:

- REMS notification;
- REM payload;
- REMS receipt; and
- REM dispatch;
- as defined in ETSI EN 319 532-1 [3].

These instances are used in clause 8 for defining different test cases.

The set of REM message instances is built following the technical approach shown below:

- The set includes instances of each type of REM message.
- For each type of REM message there is at least one instance where all the optional headers defined in ETSI EN 319 532-3 [5] are present. In the rest of test cases subsets of the aforementioned optional headers are present.
- For each type of REM message there will be at least one instance where the REM message includes all the optional MIME parts that it can include (in addition to the mandatory ones). In the rest of instances, subsets of the aforementioned optional MIME parts are present.
- The present document first defines different instances for each MIME part that can be present in one of the different types of REM message, namely: REMS relay metadata MIME Header (that includes REMS relay metadata and REMS handover metadata), introduction MIME section, original message MIME section, extensions MIME section, ERDS evidence MIME section, and S/MIME signature MIME section.
- Each instance of a certain type of REM message is defined as a composition of different MIME parts specified in the aforementioned MIME parts test cases.

The rest of the present clause is organized as follows:

Clause 6.2 presents a number of combinations of fields for the different headers that can be present in the different REM message types. These combinations are specified separately as they are used in the definition of instances of different REM message types.

Clause 6.3 defines instances of REM payloads.

Clause 6.4 defines instances of REMS notifications.

Clause 6.5 defines instances of REMS receipts.

Clause 6.6 defines instances of REM dispatches.

As mentioned in clause 4.2 new combinations of fields may be defined for each header, and new instances of REM messages may be added to the current set, for defining new test cases.

6.2 Combinations of fields for headers in REM envelopes

6.2.1 Introduction

The following clauses define combinations of headers fields for all the headers that may be present in REM envelopes, namely: the REMS relay metadata MIME Header, the signed data MIME header, the headers in REMS introduction MIME section, the original message MIME section header, the REMS extensions MIME section header, the ERDS evidence MIME section header, and the REMS signature MIME header.

6.2.2 Combinations of fields for the REMS relay metadata MIME Header

The present clause defines different combinations of fields for the REMS relay metadata MIME Header of the REM envelope.

The definition of a certain combination is split in two tables, namely Table 10 and Table 11.

Table 10 shows combinations of fields that are defined in MIME and SMIME RFCs. Only the fields listed in a certain combination shall be present in that combination. Not listed fields shall be absent.

Cells in column "Field name" contain the name of the header fields.

Cells in column "Value" shows the value to be assigned to the header field. These cells may contain the following values:

- As specified in ETSI EN 319 532-3 [5]. This value is reserved for cases where ETSI EN 319 532-3 [5] specifies a mandatory value for the header field.
- As recommended in ETSI EN 319 532-3 [5]. This value is reserved for cases where ETSI EN 319 532-3 [5] recommends one certain value for the header field (usually using the modal verb should). In these cases, the header field has this recommended value in the combination.
- AS_PER_TESTCASE means that for this test case the tester is free to give to the aforementioned field the value it considers worth, provided that it fulfils the additional requirements indicated in Table 10.

Cells in "Notes/Additional requirements" contain one or more letters or/and one or more integer numbers. The letters correspond to additional requirements that are given after Table 10. The numbers correspond to numbers of notes that appear after the aforementioned additional requirements.

Table 10: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value	Notes/Additional requirements
RFCFields#1	Content-Type	As specified in ETSI EN 319 532-3 [5]	
	MIME-Version	As specified in ETSI EN 319 532-3 [5]	
	Message-ID	As recommended in ETSI EN 319 532-3 [5]	
	Date	As specified in ETSI EN 319 532-3 [5]	
	From	As recommended in ETSI EN 319 532-3 [5]	1
	To	As specified in ETSI EN 319 532-3 [5]	
	Subject	As recommended in ETSI EN 319 532-3 [5]	
RFCFields#2	Content-Type	As specified in ETSI EN 319 532-3 [5]	
	MIME-Version	As specified in ETSI EN 319 532-3 [5]	
	Message-ID	As recommended in ETSI EN 319 532-3 [5]	
	Date	As specified in ETSI EN 319 532-3 [5]	
	From	As recommended in ETSI EN 319 532-3 [5]	1
	To	As specified in ETSI EN 319 532-3 [5]	
	Cc	As recommended in ETSI EN 319 532-3 [5]	
	Subject	As recommended in ETSI EN 319 532-3 [5]	
	Reply-To	As specified in ETSI EN 319 532-3 [5]	
	Return-Path	As specified in ETSI EN 319 532-3 [5]	
	Received	As specified in ETSI EN 319 532-3 [5]	
In-Reply-To	As recommended in ETSI EN 319 532-3 [5]		

NOTE 1: "From" header field is mandatory but ETSI EN 319 532-3 [5] recommends two ways of computing its value. The corresponding test cases for REM message formats will be in charge of selecting one of them. As it is expected that each REMS opts for one of the two mechanisms, and selecting one or the other does not introduce any hinder to interoperability, selecting one or the other does not result in a different test case.

Table 11 shows the combinations of the new header fields defined in ETSI EN 319 532-3 [5].

For the purpose of defining the test cases, the field "REM-ApplicablePolicy" shall always consist in a single URI and consequently, its formatting does not require creation of one MIME extension section as specified in ETSI EN 319 532-3 [5], clause 6.2.5. New combinations may be added where this field consists in a sequence of URIs and its structured value be placed in the corresponding extension MIME section.

Cells in "Header field name" column contain the name of a field in the REMS relay metadata MIME Header. The names used are the ones defined in ETSI EN 319 532-3 [5] and (whenever required) in the different RFCs specifying MIME and S/MIME formats (references [7], [8], [9], [10], [11], [12], [13] and [14]).

Cells in "Header field value" column contain either:

- 1) the value of the header field whose name is the one indicated in the previous column; or
- 2) AS_PER_TESTCASE, with the meaning described before.

Cells in "Notes/Additional requirements" contain one or more letters or/and one or more integer numbers. The letters correspond to additional requirements that are given after the table. The numbers correspond to numbers of notes that appear after the aforementioned additional requirements.

Cells in "Purpose" contain a description of the purpose of the combination defined in the row.

Some rows of the table though only have three columns. This happens when a certain test case is based in a test case already specified and that has only some few differences. Then only the columns "Test case identifier", "Test case based on", and "Purpose" apply for these rows. The "Test case based on" central cell contains all the relevant details for the test case, including the test case on which this one is based and the differences between both of them.

The values of these fields shall be the ones specified in the aforementioned references.

Table 11 defines parameterized combinations for new headers defined in ETSI EN 319 532-3 [5]. The combinations have as parameters the assurance levels and the consignment mode.

Table 11: First set of parameterized combinations for REMS relay metadata MIME Header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
NewFields#1	REM-RelayDate	AS_PER_TESTCASE	a, 2	Use in tests where: the contents of the fields are correct; there is no indication neither of assurance levels nor of mode of consignment
	REM-ExpirationDate	AS_PER_TESTCASE	b	
	REM-ScheduledDelivery	AS_PER_TESTCASE	c	
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#2	REM-RelayDate	AS_PER_TESTCASE	a, 2	Use in tests where: the contents of the fields are correct; the assurance levels required is one parameter, and there is no indication of mode of consignment
	REM-ExpirationDate	AS_PER_TESTCASE	b	
	REM-RecipientAssuranceLevel	Parameter		
	REM-ScheduledDelivery	AS_PER_TESTCASE	c	
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#3	REM-RelayDate	AS_PER_TESTCASE	a, 2	Use in tests where: the contents of the fields are correct; the REMS relay metadata MIME Header has all the optional fields present; and the assurance levels and the mode of consignment are parameters
	REM-ExpirationDate	AS_PER_TESTCASE	b	
	REM-RecipientAssuranceLevel	Parameter		
	REM-ModeOfConsignment	Parameter		
	REM-ScheduledDelivery	AS_PER_TESTCASE	c	
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#4	REM-RelayDate	AS_PER_TESTCASE	a, 2	Use in negative tests where: the scheduled delivery is after the expiration date; assurance levels is one parameter, and there is no indication of mode of consignment
	REM-ExpirationDate	AS_PER_TESTCASE	b	
	REM-RecipientAssuranceLevel	Parameter		
	REM-ScheduledDelivery	AS_PER_TESTCASE	d	
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#5	REM-RelayDate	AS_PER_TESTCASE	a, 2	Use in negative tests where: the scheduled delivery is after the expiration date; and the assurance levels and the mode of consignment are parameters
	REM-ExpirationDate	AS_PER_TESTCASE	b	
	REM-RecipientAssuranceLevel	Parameter		
	REM-ModeOfConsignment	Parameter		
	REM-ScheduledDelivery	AS_PER_TESTCASE	d	
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#6	REM-RelayDate	AS_PER_TESTCASE	a, 2	As NewFields#1 but without REM-ScheduledDelivery
	REM-ExpirationDate	AS_PER_TESTCASE		
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#7	REM-RelayDate	AS_PER_TESTCASE	a, 2	As NewFields#2 but without REM-ScheduledDelivery
	REM-ExpirationDate	AS_PER_TESTCASE		
	REM-RecipientAssuranceLevel	Parameter		
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#8	REM-RelayDate	AS_PER_TESTCASE	a, 2	As NewFields#3 but without REM-ScheduledDelivery
	REM-ExpirationDate	AS_PER_TESTCASE		
	REM-RecipientAssuranceLevel	Parameter		
	REM-ModeOfConsignment	Parameter		
	REM-ApplicablePolicy	AS_PER_TESTCASE		

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
NewFields#9	REM-ExpirationDate	AS_PER_TESTCASE	b	As NewFields#1 but without REM-RelayDate and without REM-ScheduledDelivery
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#10	REM-ExpirationDate	AS_PER_TESTCASE		As NewFields#2 but without REM-RelayDate and without REM-ScheduledDelivery
	REM-RecipientAssuranceLevel	Parameter		
	REM-ApplicablePolicy	AS_PER_TESTCASE		
NewFields#11	REM-ExpirationDate	AS_PER_TESTCASE		As NewFields#3 but without REM-RelayDate and without REM-ScheduledDelivery
	REM-RecipientAssuranceLevel	Parameter		
	REM-ModeOfConsignment	Parameter		
	REM-ApplicablePolicy	AS_PER_TESTCASE		
Additional requirements:				
a) The date and time indicated in this field shall be earlier than the date and time indicated in "REM-ExpirationDate" and "REM-ScheduledDelivery" (if present).				
b) The date and time indicated in this field shall be later than the date and time indicated in "REM-RelayDate" and "REM-ScheduledDelivery" (if present).				
c) The date and time indicated in this field shall be earlier than the date and time indicated in "REM-ScheduledDelivery" and later than the date and time indicated in "REM-RelayDate" (if present).				
d) The date and time indicated in this field shall be later than the date and time indicated in "REM-RelayDate" and later than "REM-ExpirationDate" (if present).				

NOTE 2: This combination can be used only in scenarios of REM messages where a REMS relays the REM message to another REMS, i.e. in situations where sender and receiver are not subscribed to the same REMS.

The present document defines the combinations of fields of the REMS relay metadata MIME Header of the REM envelope that are shown in Table 12.

Each instance of the REMS relay metadata MIME Header shown in Table 12 is defined as the aggregation of one of the combinations of RFC header fields defined in Table 10 and one of the combinations of the new header fields defined in Table 11.

Each combination defined in Table 12 has four parameters, namely:

- 1) An integer identifying the RFC headers combination.
- 2) An integer identifying the new header fields combinations.
- 3) The value of the required assurance levels (nil if this information is not present in the combination).
- 4) The consignment mode (nil if this information is not present).

The table defines a number of possible combinations of these parameters when the required assurance levels are the same for sender and entities at receiving side. It also defines combinations where the consignment mode field is not present. Finally, it also defines two illegal combinations, that can be used in negative test cases.

All the REMS relay metadata MIME Headers instances can be obtained from the following expression:

(RFCFields_id, NewFields_id, AssuranceLevelCombs, ConsignmentMode) where:

- RFCFields_id goes from 1 to 2.
- NewFields_id goes from 1 to 11.
- AssuranceLevelCombs is one of {nil, low/low, subs/subs, high/high}.
- ConsignmentMode is one of {nil, basic, consented, consentedSigned}.

Table 12 defines some combinations and their corresponding purposes.

Table 12: REM messages REMS relay metadata MIME Header combinations

Combination identifier	Combination definition	Purpose
For test cases without REM-RelayDate and without REM-ScheduledDelivery. Scenarios without message relaying		
REMSRelayMetadata(1,9,nil,nil)	RFCFields#1 + NewFields#9	No indications neither of assurance levels nor consignment mode
REMSRelayMetadata(1,10,low/low,nil)	RFCFields#1 + NewFields#10(low/low)	No consignment mode indicated and assurance level
REMSRelayMetadata(1,10,sub/subs,nil)	RFCFields#1 + NewFields#10(substantial/substantial)	
REMSRelayMetadata(1,10,high/high,nil)	RFCFields#1 + NewFields#10(high/high)	
REMSRelayMetadata (1,11,low/low,basic)	RFCFields#1 + NewFields#11(low/low, basic)	Basic consignment mode and assurance level
REMSRelayMetadata(1,11,subs/subs,basic)	RFCFields#1 + NewFields#11(substantial/substantial, basic)	
REMSRelayMetadata (1,11,high/high,basic)	RFCFields#1 + NewFields#11(high/high, basic)	
REMSRelayMetadata (1,11,low/low,consented)	RFCFields#1 + NewFields#11(low/low, consented)	Consented consignment mode and assurance level
REMSRelayMetadata(1,11,subs/subs,consented)	RFCFields#1 + NewFields#11(substantial/substantial, consented)	
REMSRelayMetadata (1,11,high/high,consented)	RFCFields#1 + NewFields#11(high/high, consented)	
REMSRelayMetadata (1,11,low/low,consentedSigned)	RFCFields#1 + NewFields#11(low/low, consentedSigned)	Consented and signed consignment mode and assurance level
REMSRelayMetadata(1,11,subs/subs,consentedSigned)	RFCFields#1 + NewFields#11(substantial/substantial, consentedSigned)	

Combination identifier	Combination definition	Purpose
REMSRelayMetadata (1,11,high/high,consentedSigned)	RFCFields#1 + NewFields#11(high/high, consentedSigned)	
For test cases without REM-ScheduledDelivery. Scenarios with message relaying		
REMSRelayMetadata(1,6,nil,nil)	RFCFields#1 + NewFields#6	No indications neither of assurance levels nor consignment mode
REMSRelayMetadata(1,7,low/low,nil)	RFCFields#1 + NewFields#7(low/low)	No consignment mode indicated and assurance level
REMSRelayMetadata(1,7,sub/subs,nil)	RFCFields#1 + NewFields#7(substantial/substantial)	
REMSRelayMetadata(1,7,high/high,nil)	RFCFields#1 + NewFields#7(high/high)	
REMSRelayMetadata (1,8,low/low,basic)	RFCFields#1 + NewFields#8(low/low, basic)	Basic consignment mode and assurance level
REMSRelayMetadata(1,8,subs/subs,basic)	RFCFields#1 + NewFields#8(substantial/substantial, basic)	
REMSRelayMetadata (1,8,high/high,basic)	RFCFields#1 + NewFields#8(high/high, basic)	
REMSRelayMetadata (1,8,low/low,consented)	RFCFields#1 + NewFields#8(low/low, consented)	Consented consignment mode and assurance level
REMSRelayMetadata(1,8,subs/subs,consented)	RFCFields#1 + NewFields#8(substantial/substantial, consented)	
REMSRelayMetadata (1,8,high/high,consented)	RFCFields#1 + NewFields#8(high/high, consented)	
REMSRelayMetadata (1,8,low/low,consentedSigned)	RFCFields#1 + NewFields#8(low/low, consentedSigned)	Consented and signed consignment mode and assurance level
REMSRelayMetadata(1,8,subs/subs,consentedSigned)	RFCFields#1 + NewFields#8(substantial/substantial, consentedSigned)	
REMSRelayMetadata (1,8,high/high,consentedSigned)	RFCFields#1 + NewFields#8(high/high, consentedSigned)	
For test cases with REM-RelayDate and with REM-ScheduledDelivery. Scenarios with message relaying		
REMSRelayMetadata(1,1,nil,nil)	RFCFields#1 + NewFields#1	No indications neither of assurance levels nor consignment mode
REMSRelayMetadata(1,2,low/low,nil)	RFCFields#1 + NewFields#2(low/low)	No consignment mode indicated and assurance level
REMSRelayMetadata(1,2,sub/subs,nil)	RFCFields#1 + NewFields#7(substantial/substantial)	
REMSRelayMetadata(1,2,high/high,nil)	RFCFields#1 + NewFields#2(high/high)	
REMSRelayMetadata (1,3,low/low,basic)	RFCFields#1 + NewFields#3(low/low, basic)	Basic consignment mode and assurance level
REMSRelayMetadata(1,3,subs/subs,basic)	RFCFields#1 + NewFields#8(substantial/substantial, basic)	
REMSRelayMetadata (1,3,high/high,basic)	RFCFields#1 + NewFields#3(high/high, basic)	
REMSRelayMetadata (1,3,low/low,consented)	RFCFields#1 + NewFields#3(low/low, consented)	Consented consignment mode and assurance level
REMSRelayMetadata(1,3,subs/subs,consented)	RFCFields#1 + NewFields#3(substantial/substantial, consented)	
REMSRelayMetadata (1,3,high/high,consented)	RFCFields#1 + NewFields#3(high/high, consented)	
REMSRelayMetadata (1,3,low/low,consentedSigned)	RFCFields#1 + NewFields#3(low/low, consentedSigned)	Consented and signed consignment mode and assurance level
REMSRelayMetadata(1,3,subs/subs,consentedSigned)	RFCFields#1 + NewFields#3(substantial/substantial, consentedSigned)	
REMSRelayMetadata (1,3,high/high,consentedSigned)	RFCFields#1 + NewFields#3(high/high, consentedSigned)	
REMSRelayMetadata (1,4,low/low,nil)	RFCFields#1 + NewFields#4(low/low)	

Combination identifier	Combination definition	Purpose
REMSRelayMetadata (1,5,low/low,basic)	RFCFields#1 + NewFields#5(low/low,basic)	Combinations for negative test cases (cause of submission rejection for instance)

Outer most headers combinations similar to the ones shown in the table but replacing 1 by 2 in the first parameter would result in combinations with RFCFields#2.

6.2.3 Combinations of fields for the signed data MIME header

In all the test cases defined in the present document this header shall be as specified in ETSI EN 319 532-3 [5], clause 6.2.2. The resulting combination of header fields will be identified as SIGDATA_COMB.

6.2.4 Combinations of fields for the REMS introduction section

6.2.4.1 Introduction

The present clause defines combinations of fields for three different headers in the REMS introduction section, namely: the REMS introduction MIME header, the multipart/alternative free text subsection header, and the multipart/alternative html subsection header.

6.2.4.2 Combinations of fields for the REMS introduction MIME header

All the test cases defined in the present shall include the "REM-Section-Type" field in this header. Its value shall be the recommended value in ETSI EN 319 532-3 [5], namely "rem_message/introduction". This combination is identified as REMS_IntrComb.

The mandatory field "REM-Content-Type" shall also be present with its value as specified in ETSI EN 319 532-3 [5].

6.2.4.3 Combinations of fields for the multipart/alternative free text subsection header

Table 13 shows the two possible combinations of fields for the multipart/alternative free text subsection header derived from ETSI EN 319 532-3 [5] specifications, namely one with the "Content-Disposition" field present and one without the "Content-Disposition" field.

Columns in Table 13 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10.

Table 13: Combinations for the multipart/alternative free text subsection header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
FreeText#1	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination with Content-Disposition optional field present
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as recommended in ETSI EN 319 532-3 [5]		
FreeText#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without Content-Disposition optional field
	Content-Transfer-Encoding	as recommended in ETSI EN 319 532-3 [5]		

6.2.4.4 Combinations of fields for the multipart/alternative html subsection header

All the test cases defined in the present document shall include the two mandatory header fields ("Content-Type" and "Content-Transfer-Encoding") in the multipart/alternative html subsection header, with the values specified in ETSI EN 319 532-3 [5]. This combination is identified as HTMLComb.

6.2.5 Combinations of fields for the original message MIME section header

Table 14 shows three combinations of fields for the original message section header derived from ETSI EN 319 532-3 [5] specifications.

Columns in Table 14 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10 and the values in column "Value" in Table 11.

Table 14: Combinations for the original message MIME section header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
OrMess#1	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination with all the optional fields present
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Description	AS_PER_TESTCASE		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
OrMess#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without Content-Description optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
OrMess#3	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without any optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		

6.2.6 Combinations of fields for one REMS extension MIME section header

Table 15 shows three combinations of fields for one REMS extension MIME section header derived from ETSI EN 319 532-3 [5] specifications.

Columns in Table 15 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10 and the values in column "Value" in Table 11.

Table 15: Combinations for one REMS extension MIME section header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
Ext#1	Content-Type	as recommended in ETSI EN 319 532-3 [5]		Combination with all the optional fields present
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Description	AS_PER_TESTCASE		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
	REM-Extension-Code	AS_PER_TESTCASE		
Ext#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without REM-Extension-Code and REM-Extension-Namespace-URI optional fields
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Description	AS_PER_TESTCASE		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
Ext#3	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without any optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		

6.2.7 Combinations of fields for one ERDS evidence MIME section header

6.2.7.1 Combinations of fields for one XML ERDS evidence MIME section header

Table 16 shows three combinations of fields for one ERDS evidence MIME section header derived from ETSI EN 319 532-3 [5] specifications when the ERDS evidence is in XML format.

Columns in Table 16 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10 and the values in column "Value" in Table 11.

Table 16: Combinations for one XML ERDS evidence MIME section header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
EVID#1	Content-Type	as recommended in ETSI EN 319 532-3 [5]		Combination with all the optional fields present
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Description	AS_PER_TESTCASE		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
EVID#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without Content-Description optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
EVID#3	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without any optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		

6.2.7.2 Combinations of fields for one PDF ERDS evidence MIME section header

Table 17 shows three combinations of fields for one ERDS evidence MIME section header derived from ETSI EN 319 532-3 [5] specifications when the ERDS evidence is a PDF document.

Columns in Table 17 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10 and the values in column "Value" in Table 11.

NOTE: The identifiers for these combinations are identical to the identifiers for combinations of fields in headers of ERDS evidence sections containing XML ERDS evidence. This does not introduce any ambiguity in the present document, as the clauses that define test cases assign to each test case a unique identifier that includes a component indicating whether the ERDS evidence present in a certain REMS notification, REMS receipt, or REM dispatch are XML or PDF ERDS evidence.

Table 17: Combinations for one PDF ERDS evidence MIME section header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
EVID#1	Content-Type	as recommended in ETSI EN 319 532-3 [5]		Combination with all the optional fields present
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Description REM-Section-Type	AS_PER_TESTCASE as recommended in ETSI EN 319 532-3 [5]		
EVID#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without Content-Description optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	REM-Section-Type	as recommended in ETSI EN 319 532-3 [5]		
EVID#3	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without any optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		

6.2.8 Combinations of fields for the REMS signature MIME section header

Table 18 shows combinations of fields for the REMS signature section header derived from ETSI EN 319 532-3 [5] specifications, namely one with the "Content-Description" field present and one without the "Content-Description" field.

Columns in Table 18 are identical to columns in Table 11. Values in "Header field value" have the same semantics as the values in column "Value" in Table 10. In addition to that, a value enclosed in "" represents a literal value required for the field being dealt with.

Table 18: Combinations for the multipart/alternative free text subsection header

Combination identifier	Header field name	Header field value	Notes/Additional requirements	Purpose
Sig#1	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination with all the optional fields present
	Content-Transfer-Encoding	as specified in ETSI EN 319 532-3 [5]		
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
	Content-Description	"S/MIME Cryptographic Signature"		
Sig#2	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without Content-Description optional field
	Content-Transfer-Encoding	as recommended in ETSI EN 319 532-3 [5]		
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		
Sig#3	Content-Type	as specified in ETSI EN 319 532-3 [5]		Combination without any optional field
	Content-Disposition	as specified in ETSI EN 319 532-3 [5]		

6.3 Instances of REM payload

The present clause defines instances of REM payloads for being used in test cases.

Cells in column "Instance" shows the specific instance of REM payload and all its parametrized components. Each instance is the aggregation of one of the instances of the outmost header defined in clause 6.2.2 and a list of MIME sections. Each section is the aggregation of a MIME header and a MIME body. The MIME headers will be instances of the MIME headers as specified in clauses 6.2.3 to 6.2.8. Each REM payload instance is composed by the following components:

- the REMS relay metadata MIME Header;
- the REM Introduction MIME section;
- the Free Text MIME section;
- the HTML Text MIME section;
- the Original Message MIME section;
- the Signature MIME section; and
- the optional Extension MIME section.

Each cell in column "Instance" identifies several REM payload instances, which have certain aspects in common and some other aspects that are different. This is achieved as indicated below:

The content of a cell in column "Instance" has the following pattern:

```
"REM_payloadInst  
(REMSRelayMetadata(RFCFields#I,NewFields#J,<AssLevel>,<Consignment>),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M)"
```

Where I, J, K, L, and M are integers. Assigning a value to I one of the existing combinations for RFCFields is selected (for instance RFCFields#1). Assigning a value to J one of the existing combinations for NewFields is selected (for instance NewFields#2). Assigning a value to K one of the existing combinations for FreeText is selected (for instance FreeText#1). Assigning a value to L one of the existing combinations for original message MIME section header is selected (for instance OrMess#1). Finally, assigning value to M one of the existing combinations for Signature MIME section header is selected (for instance OrMess#1).

<AssLevel> provides information on the assurance levels combinations, and can take as value either:

- nil, indicating that the header fields for indicating assurance levels are absent; OR
- "AssLevelComb", indicating that this parameter can take several values, each one corresponding to a combination of assurance levels.

<Consignment> provides information on the consignment mode, and can take as value either:

- nil, indicating that the header fields for indicating consignment mode is absent; OR
- "ConsignmentModeId", indicating that this parameter can take several values, each one corresponding to one specific consignment mode.

The aforementioned pattern is followed by text providing information of the values that I, J, K, L, M, "AssLevelComb" (if present), and "ConsignmentModeId" (if present) can take. The aforementioned pattern with this additional piece of information identifies a certain number of REM payloads in one unique cell.

For instance, a cell containing the following text:

REM_payloadInst
(REMSRelayMetadata(RFCFields#I,NewFields#J,nil,nil),REMSIntrCom,FreeText#K,OrMess#L,Sig#M) where

Where:

I is one of {1,2}, J is one of {1, 6,9}, K is one of {1,2}, L is one of {1,2,3} and M is one of {1,2,3}

Would identify all those REM payloads built when:

- RFCFields#I is one of { RFCFields#1, RFCFields#2};
- NewFields#J is one of {NewFields#1, NewFields#6, NewFields#9};
- FreeText#K is one of {FreeText#1, FreeText#2};
- OrMess#L is one of {OrMess#1, OrMess#2, OrMess#3}; and
- Sig#M is one of {Sig#1, Sig#2, Sig#3}.

Similarly, a cell containing the following text:

REM_payloadInst
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M)

Where:

I is one of {1,2}, J is one of {3,8,11}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {basic,consented,consentedSigned}, L is one of {1,2,3} and M is one of {1,2,3}

Would identify all those REM payloads built when:

- RFCFields#I is one of { RFCFields#1, RFCFields#2};
- NewFields#J is one of {NewFields#3, NewFields#8, NewFields#11};
- AssLevelComb is one of the following combinations {low/low, substantial/substantial, high/high};
- ConsignmentModeId is one of {basic,consented,consentedSigned};
- FreeText#K is one of {FreeText#1, FreeText#2};
- OrMess#L is one of {OrMess#1, OrMess#2, OrMess#3}; and
- Sig#M is one of {Sig#1, Sig#2, Sig#3}.

Cells in "Purpose" column contain a description of the purpose of the REM payload instance.

Table 19: Instances of REM payload

Instance	Purpose
<p>REM_payloadInst (REMSRelayMetadata(RFCFields#I,NewFields#J,nil,nil),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {1,6,9}, K is one of {1,2}, L is one of {1,2,3} and M is one of {1,2,3}</p>	<p>No assurance levels indication.</p> <p>No consignment indication.</p> <p>No extension as there are not structured-valued fields in the headers</p> <p>REM payloads where J is 1: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 6: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 9: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_payloadInst (REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,nil),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {2,7,10}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, L is one of {1,2,3} and M is one of {1,2,3}</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending of the value of parameter AssLevelComb.</p> <p>No consignment indication.</p> <p>No extensions.</p> <p>REM payloads where J is 2: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 7: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 10: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_payloadInst (REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModelId),REMSIntrCom,FreeText#K,HTMLComb, OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {3,8,11}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, ConsignmentModelId is one of {basic,consented,consentedSigned}, L is one of {1,2,3}</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending of the value of parameter AssLevelComb.</p> <p>Consignment mode indication (either basic, or consented, or consentedSigned) depending of the value of parameter ConsignmentModelId.</p> <p>No extensions.</p> <p>REM payloads where J is 3: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 8: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM payloads where J is 11: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_payloadInst (REMSRelayMetadata(RFCFields#I,NewFields#4,AssLevelComb,nil),REMSIntrCom,FreeText#K, HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {4,5}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, L is one of {1,2,3} and M is one of {1,2,3}</p> <p>REM_payloadInst (REMSRelayMetadata(RFCFields#I,NewFields#5,AssLevelComb,ConsignmentModelId),REMSIntrCom,FreeText#K, HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {4,5}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, ConsignmentModelId is one of {basic,consented,consentedSigned}, L is one of {1,2,3} and M is one of {1,2,3}</p>	<p>Payloads for negative test cases.</p> <p>All of them incorporate REM-RelayDate header field.</p> <p>Negative test cases because scheduled delivery time is after the expiration date. No consignment indication.</p> <p>No extensions.</p> <p>Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present.</p> <p>REM payloads where J is 4: No consignment mode indication.</p> <p>REM payloads where J is 5: Consignment mode indication as per value of parameter ConsignmentModelId.</p>

6.4 Instances of REMS notification

Table 20 defines instances of REM notifications for being used in test cases. Columns are as in clause 6.3.

The notation for the content of cells in column "Instances" is as indicated in clause 6.3, with the addition that the instances of REMS notifications include Extension MIME sections, and the identification of the specific Extension MIME section follows the same principles as other MIME sections.

Table 20: Instances of REMS notification

Instance	Purpose
<p>REMS_NotificationInst (REMSRelayMetadata (RFCFields#I,NewFields#J,nil,nil),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,Sig#M) Where: I is one of {1,2}, J is one of {1,6,9}, K is one of {1,2}, L is one of {1,2,3}, and M is one of {1,2,3}</p>	<p>No assurance levels indication.</p> <p>No consignment indication.</p> <p>REMS notifications where J is 1: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 6: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 9: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REMS_NotificationInst (REMSRelayMetadata (RFCFields#I,NewFields#J,nil,nil),REMSIntrComb,FreeText#K,HTMLComb,Sig#L)</p> <p>Where: I is one of {1,2}, J is one of {1,6,9}, K is one of {1,2}, and L is one of {1,2,3}</p>	<p>No assurance levels indication.</p> <p>No consignment indication.</p> <p>No extension as there are not structured-valued fields in the headers</p> <p>REMS notifications where J is 1: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 6: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 9: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REMS_notificationInst (REMSRelayMetadata (RFCFields#I,NewFields#J,AssLevelComb,nil),REMSIntrCom,FreeText#K,HTMLComb,Ext#L,Sig#M)</p> <p>Where: I is one of {1,2}, J is one of {2,7,10}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, L is one of {1,2,3}, and M is one of {1,2,3}</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending on the value of parameter AssLevelComb.</p> <p>No consignment indication.</p> <p>REMS notifications where J is 2: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 7: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 10: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REMS_notificationInst (REMSRelayMetadata (RFCFields#I,NewFields#J,AssLevelComb,nil),REMSIntrCom,FreeText#K,HTMLComb, Sig#L)</p> <p>Where: I is one of {1,2}, J is one of {2,7,10}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, and L is one of {1,2,3}</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending on the value of parameter AssLevelComb.</p> <p>No consignment indication.</p> <p>No extensions.</p> <p>REMS notifications where J is 2: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 7: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REMS notifications where J is 10: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

6.5 Instances of REMS receipts

Table 21 defines instances of REMS receipts for being used in test cases. Columns are as in clause 6.3.

A REMS receipt can have more than one ERDS evidence MIME section. The number and contents of these MIME sections will depend on the specific test case.

Table 21: Instances of REMS receipt

Instance	Purpose
<p>REMS_ReceiptInst (REMSRelayMetadata (RFCFields#I,NewFields#J,nil,nil),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N)</p> <p>Where: I is one of {1,2}, J is one of {1,6,9}, K is one of {1,2}, L is one of {1,2,3}, M is one of {1,2,3}, and N is one of {1,2,3}. Additionally, the + symbol in <EVID#M> indicates that in each case, the REMS receipt instance shall contain as many Evidence MIME sections as Evidence MIME sections are indicated in the test case where the REMS receipt is used. This unique content identifies all the possible REMS receipts that will be needed in the definitions of the test cases.</p>	<p>No assurance levels indication.</p> <p>No consignment indication.</p> <p>REMS receipts where J is 1: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REMS receipts where J is 6: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REMS receipts where J is 9: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

6.6 Instances of REM dispatch

Table 22 defines instances of REM dispatches for being used in test cases. Columns are as in clause 6.3. Details of the ERDS evidence MIME sections are indicated as in clause 6.5.

Table 22: Instances of REM dispatch

Instance	Purpose
<p>REM_dispatchInst (REMSRelayMetadata (RFCFields#I,NewFields#J,nil,nil),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Ext#M,<EVID#N>+,Sig#O)</p> <p>Where: I is one of {1,2}, J is one of {1,6,9}, K is one of {1,2}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}. As before the symbol + in <EVID#M>+ indicates that there will be as many Evidence MIME sections as the sections indicated in the test case using this REM dispatch.</p>	<p>No assurance levels indication.</p> <p>No consignment indication.</p> <p>No extensions</p> <p>REM dispatches where J is 1: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 6: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 9: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_dispatchInst (REMSRelayMetadata (RFCFields#I,NewFields#J,AssLevelComb,nil),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Ext#M,<EVID#N>+,Sig#O)</p> <p>Where: I is one of {1,2}, J is one of {2,7,10}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}. As before the symbol + in <EVID#M>+ indicates that there will be as many Evidence MIME sections as the sections indicated in the test case using this REM dispatch.</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending on the value of parameter AssLevelComb.</p> <p>No consignment indication.</p> <p>No extensions.</p> <p>REM dispatches where J is 2: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 7: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 10: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_dispatchInst REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModelId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Ext#M,<EVID#N>+,Sig#O)</p> <p>Where: I is one of {1,2}, J is one of {3,8,11}, K is one of {1,2}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, ConsignmentModelId is one of {basic,consented,consentedSigned}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}. As before the symbol + in <EVID#M>+ indicates that there will be as many Evidence MIME sections as the sections indicated in the test case using this REM dispatch.</p>	<p>Assurance levels indications (either low/low, or substantial/substantial, or high/high) depending on the value of parameter AssLevelComb.</p> <p>Consignment mode indication (either basic, or consented, or consentedSigned) depending of the value of parameter ConsignmentModelId.</p> <p>No extensions.</p> <p>REM dispatches where J is 3: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 8: Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present. Do not incorporate REM-RelayDate header field.</p> <p>REM dispatches where J is 11: Cannot be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is absent. Do not incorporate REM-RelayDate header field.</p>

Instance	Purpose
<p>REM_payloadInst (REMSRelayMetadata (RFCFields#I,NewFields#4,AssLevelComb,nil),REMSIntrCom,FreeText#K, HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {4,5}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, L is one of {1,2,3} and M is one of {1,2,3}</p> <p>REM_payloadInst (REMSRelayMetadata (RFCFields#I,NewFields#5,AssLevelComb,ConsignmentModeld),REMSIntrCom,FreeText#K, HTMLComb,OrMess#L,Sig#M) Where: I is one of {1,2}, J is one of {4,5}, AssLevelComb is one of {low/low, substantial/substantial, high/high}, ConsignmentModeld is one of {basic,consented,consentedSigned}, L is one of {1,2,3} and M is one of {1,2,3}</p>	<p>Payloads for negative test cases.</p> <p>All of them incorporate REM-RelayDate header field.</p> <p>Negative test cases because scheduled delivery time is after the expiration date. No consignment indication.</p> <p>No extensions.</p> <p>Will be used in scenarios where there is relaying of REM messages, as the REM-RelayDate header field is present.</p> <p>REM payloads where J is 4: No consignment mode indication.</p> <p>REM payloads where J is 5: Consignment mode indication as per value of parameter ConsignmentModeld.</p>

7 Other named sets

7.1 Named sets of participating REMSs

The present clause defines named sets of participating REMSs that are used for naming test cases in clause 5.

The details on the participating REMSs are given using the following pattern: REMSs(I,J), where:

- I stands for the number of Intermediate REMSs (IREMSs); and
- J stands for the number of the Recipient's REMSs (RREMSs).

7.2 Named sets of additional requirements

The present clause defines named sets of additional requirements that are used for building different test cases based on the same scenarios of REM messages.

Table 23 shows the named sets of additional requirements.

Table 23: Named sets of additional requirements

Name of the set	Additional requirements in the set
AdditionalReqs#1	Original message: not signed, no attachment
	Number of recipients: 1
	No sender's delegate
	Sender sends original message
AdditionalReqs#2	Original message: not signed, no attachment
	Number of recipients: 1
	Sender's delegate sends original message

7.3 Named sets of entities in receiving side

The present clause defines named sets of entities that are present at receiving side. This allows using one scenario in defining different test cases by changing the entities in the receiving side.

EXAMPLE: Scenarios defined for one recipient could be used in test cases where the scenarios involve only one delegate of one recipient.

In order to define the names of the sets, the pattern RecSide(I, J, K) is used where:

- I stands for the number of recipients.
- J stands for the number of recipient's delegates.
- K stands for the number of recipients each delegate is delegate of.

K shall always be less or equal than I. If I is not 0 then K shall also be different from 0.

8 Test cases definition

8.1 Introduction

The notations shown in clauses 4.1, 6 and 7, allow building a compact notation for defining tests cases.

The present document defines sets of test cases. Each set of test cases is expressed as a function of a number of parameters (some of them are integers, other are tuples of several values, other -mainly reasons for failures- are enumerated values specified in another ETSI deliverable).

Under these conditions one specific test case is obtained when the set is particularized by assigning a single value to each parameter.

For helping in understanding the notation, below follows the definition of the set of test cases for the scenario REM_SF#3. The definition of a set of test cases has two parts. Below follows the first one:

```
REM_SF#3(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_XML_SUB_REJ
(REMSRelayMetadata (RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P
)
```

This part shows the components required for defining the test cases for this scenario. For this scenario each test case in the set will require providing details of:

- 1) The entities in the receiving side (RecSide). The notation for identifying one of the different alternatives is as specified in clause RECEIVING SIDE.
- 2) The REM Dispatch instance, which also carries an ERDS Evidence (XML_SUB_ACC). The notation for completely defining one specific instance among all the possibilities offered by the different parameters, is as specified in clause REMDISPATCH.
- 3) The REMS Receipt, carrying a XML_SUB_ACC ERDS evidence. The notation for completely defining one specific instance among all the possibilities offered by the different parameters, is as specified in clause REMSEVIDENCE.
- 4) The additional requirements, whose notation has been specified in clause ADDITIONALREQS.

Some scenarios include REM payloads instead of REM dispatches. The details of the components of a REM payload are provided as the details of components of a REM dispatch.

Below follows the second part of the definition of the set of test cases:

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}. For AdditionalReqs: P is one of {1,2}.

This part shows the different values that the parameters present in the first part, can have.

Each legal combination of all the parameters will collapse the set in ONE test case. For instance:

```
RecSide(1,0,0),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#1, NewFields#11, high/high,
consentedSigned),REMSIntrCom,FreeText#1,HTMLComb,OrMess#1, Ext#1,<EVID#1>,Sig#1),
REMS_receipt_with_XML_SUB_REJ
(REMSRelayMetadata(RFCFields#1, NewFields#9 nil,
nil),REMSIntrComb,FreeText#1,HTMLComb,Ext#1,<EVID#1>+,Sig#1),
AdditionalReqs#P
```

Defines ONE test case in the set, where:

- The REM-RelayDate and REM-ScheduledDelivery header fields are absent in the REMS relay metadata MIME Header of the REM Dispatch and the REMS Receipt (NewFields#11 combination of new header fields).
- The assurance level combination indication is present and its value is high/high.
- The consignment mode indication is present and its value is consentedSigned.
- The headers in Free Text, Extension, Evidence, and Signature MIME extensions are as indicated in the corresponding clauses defining combinations of header fields for these MIME sections, when the parameter in all of them is 1.

8.2 Test cases for black-box model

8.2.1 Test cases for Store&Forward style of operation

8.2.1.1 Introduction

The present clause defines a set of test cases for each scenario defined in clause XXX (Store&Forward style of operation in the black-box model).

Below follow some remarks that apply to all the sets defined in the present clause:

- All the scenarios do not deal with relaying of REM messages. REM-RelayDate header field is absent (i.e. the valid combination of NewFields are #9 to #11).
- Each set includes test cases for different sets of entities at the receiving side (one or several recipients, and several recipients and one recipients' delegate).
- Each set includes test cases for sender and test cases for sender's delegate.

Below follow a set of rules that govern the values of NewFields#J, Assurance levels indication, and Consignment mode indication:

- 1) Absence of Assurance levels indication is indicated by a nil value.
- 2) Absence of Consignment mode indication is indicated by a nil value.
- 3) For NewFields#9 neither Assurance levels indication nor Consignment mode indication are present.
- 4) For NewFields#10 Assurance levels indication is present, and Consignment mode indication is absent.
- 5) For NewFields#11 both Assurance levels indication, and Consignment mode indication are present.

Any combination (NewFields#J, AssLevelComb, ConsignmentModeId) in a specific test case has to meet the rules 3 to 4.

This clause defines, for this model and style of operation, one set of test cases with the details shown above.

For other styles and models, the present document will present rules for defining such sets, as defining one set for each scenario would make the present document extremely long, and the specific definition of one set of test cases for one specific scenario will be straightforward applying the aforementioned rules.

8.2.1.2 Test cases for scenario REM_SF#1

```
REM_SF#1(
  RecSide(F,G,H),
  REMS_receipt_with_XML_SUB_REJ
  (REMSRelayMetadata(RFCFields#I,NewFields#J, AssLevelComb,
  ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
  AdditionalReqs#P,
  FailureReason
)
```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REMS_receipt_with_XML_SUB_REJ:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, and N is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RA02,RA03,RD04,RA05 } as defined in clause 8.3.3.1 of ETSI EN 319 522-2 [2].

8.2.1.3 Test cases for scenario REM_SF#2

```
REMSF#2(
  RecSide(F,G,H),
  REMS_receipt_with_{2 XML_SUB_REJ}
  (REMSRelayMetadata(RFCFields#I,NewFields#J, AssLevelComb,
  ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
  AdditionalReqs#P,
  FailureReason
)
```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REMS_receipt_with_{2 XML_SUB_REJ}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, K is one of {1,2,3}, L is one of {1,2,3}, M is one of {1,2,3}, and N is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RA02,RA03,RD04,RA05 } as defined in clause 8.3.3.1 of ETSI EN 319 522-2 [2]. Failure reasons in REMS receipts will be different.

8.2.1.4 Test cases for scenario REM_SF#3

```

REM_SF#3(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_XML_SUB_REJ
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.

8.2.1.5 Test cases for scenario REM_SF#4

```

REM_SF#4(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_CONS_FAIL}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P,
FailureReason
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_CONS_FAIL}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RD03,RD04,RD05,RD06} as defined in clause 8.3.3.4 of ETSI EN 319 522-2 [2].

8.2.1.6 Test cases for scenario REM_SF#5

```

REM_SF#5(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, 2 XML_CONT_CONS_FAIL}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P,
FailureReason
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, 2 XML_CONT_CONS_FAIL}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RD03,RD04,RD05,RD06} as defined in clause 8.3.3.4 of ETSI EN 319 522-2 [2].

8.2.1.7 Test cases for scenario REM_SF#6

```

REM_SF#6(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.

8.2.1.8 Test cases for scenario REM_SF#7

```

REM_SF#7(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, XML_CONT_HAND_FAIL}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P,
FailureReason
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.

- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, XML_CONT_HAND_FAIL}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RE03,RE04 } as defined in clause 8.3.3.5 of ETSI EN 319 522-2 [2].

8.2.1.9 Test cases for scenario REM_SF#8

```

REM_SF#8(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, 2 XML_CONT_HAND_FAIL}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P,
FailureReason
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONT_HAND, 2 XML_CONT_HAND_FAIL}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is one of {RE03,RE04 } as defined in clause 8.3.3.5 of ETSI EN 319 522-2 [2].

8.2.1.10 Test cases for scenario REM_SF#9

```

REM_SF#9(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC,XML_CONS_NOT, XML_CONT_CONS}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
REMS_notification_of_Consignment
(REMSRelayMetadata(RFCFields#I,NewFields#10,
AssLevelComb,nil),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,Sig#M),
AdditionalReqs#P
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.

- For REM_dispatchInst_with_XML_SUB_ACC, REMS_receipt_with_{XML_SUB_ACC,XML_CONS_NOT, XML_CONT_CONS}, and REMS_notification_of_Consignment:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned },L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.

8.2.1.11 Test cases for scenario REM_SF#10

```
REM_SF#10(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, XML_CONS_NOT_FAIL }
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
REMS_notification_of_Consignment
(REMSRelayMetadata(RFCFields#I, NewFields#10,
AssLevelComb,nil),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,Sig#M),
AdditionalReqs#P,
ReasonFailure
)
```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_dispatchInst_with_XML_SUB_ACC, REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, XML_CONS_NOT_FAIL}, and REMS_notification_of_Consignment:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned },L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is identified by one of the codes defined in clause 8.3.3.4 of ETSI EN 319 522-2 [2].

8.2.1.12 Test cases for scenario REM_SF#11

```
REM_SF#11(
RecSide(F,G,H),
REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L, Ext#M,<EVID#N>,Sig#O),
REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, 2 XML_CONS_NOT_FAIL }
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb,
ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
REMS_notification_of_Consignment
(REMSRelayMetadata(RFCFields#I, NewFields#10,
AssLevelComb,nil),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,Sig#M),
AdditionalReqs#P,
ReasonFailure
)
```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.

- For REM_dispatchInst_with_XML_SUB_ACC, REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS, XML_CONS_NOT, 2 XML_CONS_NOT_FAIL }, and REMS_notification_of_Consignment:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.
- FailureReason is identified by one of the codes defined in clause 8.3.3.4 of ETSI EN 319 522-2 [2].

8.2.1.13 Test cases for scenario REM_SF#12

```

REM_SF#12(
RecSide(F,G,H),
REM_payloadInst
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M)
REMS_receipt_with_XML_SUB_ACC,
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
REMS_receipt_with_{XML_SUB_ACC,XML_CONT_CONS}
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_payloadInst, REMS_receipt_with_XML_SUB_ACC, and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, K is one of {1,2}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.
- For AdditionalReqs: P is one of {1,2}.

8.2.1.14 Test cases for scenario REM_SF#13

```

REM_SF#13(
RecSide(F,G,H),
REM_payloadInst
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrCom,FreeText#K,HTMLComb,OrMess#L,Sig#M)
REMS_receipt_with_XML_SUB_ACC,
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
REMS_receipt_with_XML_CONT_CONS
(REMSRelayMetadata(RFCFields#I,NewFields#J,AssLevelComb,ConsignmentModeId),REMSIntrComb,FreeText#K,HTMLComb,Ext#L,<EVID#M>+,Sig#N),
AdditionalReqs#P
)

```

Where:

- For RecSide: (F,G,H) is one of {(1,0,0), (3,0,0), (3,1,2),(3,1,3)}: define test cases for one recipient, several recipients, and several recipients and one recipient's delegate.
- For REM_payloadInst, REMS_receipt_with_XML_SUB_ACC, and REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}:
 - I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, K is one of {1,2}, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.

- For AdditionalReqs: P is one of {1,2}.

8.2.2 Test cases for Store&Notify style of operation

8.2.2.1 Rules for REM messages

The following rules will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios REM_SN#1 to REM_SN#4:

REM dispatches with ERDS Evidences will be built on the following components:
 (REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb, ConsignmentModeId), REMSIntrCom, FreeText#K, HTMLComb, OrMess#L, Ext#M, <EVID#N>, Sig#O)

Where:

- I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.

REM receipts with ERDS Evidences or sets of ERDS Evidences will be built on the following components:

REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}
 (REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb, ConsignmentModeId), REMSIntrComb, FreeText#K, HTMLComb, Ext#L, <EVID#M>+, Sig#N)

Where:

- I is one of {1,2}, J is one of {9,10,11}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.

REMS_notification_for_Acceptance will be built on the following components:
 (REMSRelayMetadata(RFCFields#I, NewFields#10, AssLevelComb, nil), REMSIntrComb, FreeText#K, HTMLComb, Ext#L, Sig#M)

Where:

- I is one of {1,2}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, L is one of {1,2,3}, and M is one of {1,2,3}.

8.2.2.2 Rules for failure reasons

The following FailureReason codes will be used for the (black-box model/Store&Notify style):

- 1) In scenario REMS_SN#2, one of the receiving entities rejects consignment. One XML_CONS_REJ ERDS evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is RC08 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].
- 2) In scenario REMS_SN#3, one of the receiving entities does not answer in time to the notification for acceptance. One XML_ACC_REJ_EXP ERDS evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is RC09 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].

8.3 Test cases for 4-corner model

8.3.1 Introduction and general rules

In this model, SREMS relays REM messages to the RREMS.

Below follow a set of rules that govern the values of NewFields#J, Assurance levels indication, and Consignment mode indication:

- 1) For NewFields#1 and NewFields#4 neither Assurance levels indication nor Consignment mode indication are present.

- 2) For NewFields#2 and NewFields#5 Assurance levels indication is present, and Consignment mode indication is absent.
- 3) For NewFields#3 and NewFields#6 both Assurance levels indication, and Consignment mode indication are present.

Any combination (NewFields#J, AssLevelComb, ConsignmentModeId) in a specific test case has to meet the rules 3 to 4.

8.3.2 Test cases for Store&Forward to Store&Forward scenarios

8.3.2.1 Rules for REM messages

The following rules will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios SREMS_SF_RREMS_SF#1 to SREMS_SF_RREMS_SF#5:

REM dispatches that are relayed from SREMS to RREMS and REM dispatches that are generated by RREMS from REM dispatches that have been relayed by the SREMS will be built on the following components: (REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb, ConsignmentModeId), REMSIntrCom, FreeText#K, HTMLComb, OrMess#L, Ext#M, <EVID#N>, Sig#O)

Where:

- I is one of {1,2}, J is one of {1,2,3,4,5,6}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.

REM receipts with ERDS Evidences or sets of ERDS Evidences will be built on the following components:

REMS_receipt_with_{XML_SUB_ACC, XML_CONT_CONS}
(REMSRelayMetadata(RFCFields#I, NewFields#J, AssLevelComb, ConsignmentModeId), REMSIntrComb, FreeText#K, HTMLComb, Ext#L, <EVID#M>+, Sig#N)

Where:

- I is one of {1,2}, J is one of {1,2,3,4,5,6}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, ConsignmentModeId is one of {nil, basic, consented, consentedSigned }, L is one of {1,2,3}, M is one of {1,2,3}, N is one of {1,2,3}, and O is one of {1,2,3}.

REMS_notification_for_XY will be built on the following components:

(REMSRelayMetadata(RFCFields#I, NewFields#10, AssLevelComb, nil), REMSIntrComb, FreeText#K, HTMLComb, Ext#L, Sig#M)

Where:

- I is one of {1,2}, AssLevelComb is one of {nil, low/low, substantial/substantial, high/high}, L is one of {1,2,3}, and M is one of {1,2,3}.

8.3.2.2 Rules for failure reasons

The following FailureReason codes will be used for the (4-corner model/Store&Forward to Store&Forward):

- 1) In scenario SREMS_SF_RREMS_SF#1, RREMS rejects relaying of the REM dispatch generated by SREMS. One XML_REL_REJ ERDS evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is one of {RB02, RB03, RB04, RB05, RB06, RB02} as specified in clause 8.3.3.2 of ETSI EN 319 522-2 [2].
- 2) In scenario SREMS_SF_RREMS_SF#4, one of the handovers by a receiving entity fails. One XML_CONT_HAND_FAIL evidence is generated. For this scenario the reason for failure code is one of {RE03, RE04} as specified in clause 8.3.3.5 of ETSI EN 319 522-2 [2].
- 3) In scenario SREMS_SF_RREMS_SF#5, one of the consignments to a receiving entity fails. One XML_CONT_CONS_FAIL evidence is generated. For this scenario the reason for failure code is one of {RD04, RD05, RD06} as specified in clause 8.3.3.4 of ETSI EN 319 522-2 [2].

8.3.3 Test cases for Store&Forward to Store&Notify scenarios

8.3.3.1 Rules for REM messages

The rules that will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios SREMS_SF_RREMS_SN#1 to SREMS_SF_RREMS_SN#5 shall be the same as the rules defined in clause 8.3.2.1 for Store&Forward to Store&Forward scenarios.

8.3.3.2 Rules for failure reasons

The following FailureReason codes will be used for the (4-corner model/Store&Forward to Store&Notify):

- 1) In scenario SREMS_SF_RREMS_SN#2, one receiving entity rejects consignment. One XML_CONS_REJ ERDS evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is RC08 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].
- 2) In scenario SREMS_SF_RREMS_SN#3, one receiving entity does not react in time to the notification for acceptance of consignment. One XML_ACC_REJ_EXP evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is RC09 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].
- 3) In scenario SREMS_SF_RREMS_SN#4, one of the consignments to a receiving entity fails. One XML_CONT_CONS_FAIL evidence is generated. For this scenario the reason for failure code is one of {RD04, RD05, RD06} as specified in clause 8.3.3.4 of ETSI EN 319 522-2 [2].
- 4) In scenario SREMS_SF_RREMS_SN#5, one of the handovers by a receiving entity fails. One XML_CONT_HAND_FAIL ERDS Evidence is generated. For this scenario the reason for failure code is one of {RE03,RE04} as specified in clause 8.3.3.5 of ETSI EN 319 522-2 [2].

8.3.4 Test cases for Store&Notify to Store&Forward scenarios

8.3.4.1 Rules for REM messages

The rules that will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios SREMS_SN_RREMS_SF#1 to SREMS_SN_RREMS_SF#5 shall be the same as the rules defined in clause 8.3.2.1 for Store&Forward to Store&Forward scenarios.

8.3.4.2 Rules for failure reasons

The following FailureReason codes will be used for the (4-corner model/Store&Notify to Store&Forward):

- 1) In scenario SREMS_SN_RREMS_SF#2, one receiving entity rejects consignment. One XML_CONS_REJ ERDS evidence is generated and encapsulated in a REMS receipt. For this scenario the reason for failure code is RC08 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].
- 2) In scenario SREMS_SN_RREMS_SF#4, one of the consignments to a receiving entity fails. One XML_CONT_CONS_FAIL ERDS Evidence is generated. For this scenario the reason for failure code is one of {RD04, RD05, RD06} as specified in clause 8.3.3.4 of ETSI EN 319 522-2 [2].
- 3) In scenario SREMS_SN_RREMS_SF#5, one of the handovers by a receiving entity fails. One XML_CONT_HAND_FAIL ERDS Evidence is generated. For this scenario the reason for failure code is one of {RE03,RE04} as specified in clause 8.3.3.5 of ETSI EN 319 522-2 [2].

8.4 Test cases for extended model

8.4.1 Test cases for scenarios S&F->S&F->S&F

8.4.1.1 Rules for REM messages

The rules that will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios SREMS_SF_IREMS_SF_RREMS_SF#1 to SREMS_SF_IREMS_SF_RREMS_SF#5 shall be the same as the rules defined in clause 8.3.2.1 for Store&Forward to Store&Forward scenarios.

8.4.1.2 Rules for failure reasons

The following FailureReason codes will be used for the (extended model/S&F->S&F-S&F):

- 1) In scenario SREMS_SF_IREMS_SF_RREMS_SF#2, one of the consignments to a receiving entity fails. One XML_CONT_CONS_FAIL ERDS Evidence is generated. For this scenario the reason for failure code is one of {RD04, RD05, RD06} as specified in clause 8.3.3.4 of ETSI EN 319 522-2 [2].
- 2) In scenario SREMS_SF_IREMS_SF_RREMS_SF#3, one of the handovers by a receiving entity fails. One XML_CONT_HAND_FAIL ERDS Evidence is generated. For this scenario the reason for failure code is one of {RE03, RE04} as specified in clause 8.3.3.5 of ETSI EN 319 522-2 [2].
- 3) In scenario SREMS_SF_IREMS_SF_RREMS_SF#5, RREMS rejects relaying the REM dispatch received from IREMS. One XML_REL_REJ ERDS Evidence is generated. For this scenario the reason for failure code is one of {RB02, RB03, RB04, RB05, RB06} as specified in clause 8.3.3.2 of ETSI EN 319 522-2 [2].

8.4.2 Test cases for scenarios S&F->S&N->S&F

8.4.2.1 Rules for REM messages

The rules that will apply for parametrizing the REM messages, which are components of the sets of test cases for scenarios SREMS_SF_IREMS_SN_RREMS_SF#1 to SREMS_SF_IREMS_SN_RREMS_SF#3 shall be the same as the rules defined in clause 8.3.2.1 for Store&Forward to Store&Forward scenarios.

8.4.2.2 Rules for failure reasons

The following FailureReason codes will be used for the (extended model/S&F->S&N-S&F):

- 1) In scenario SREMS_SF_IREMS_SN_RREMS_SF#2, one of the receiving entities rejects consignment. One XML_CONS_REJ ERDS Evidence is generated. For this scenario the reason for failure code is RC08 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].
- 2) In scenario SREMS_SF_IREMS_SF_RREMS_SF#3, one of the receiving entities rejects consignment, and the handovers by another entity fails. One XML_CONS_REJ and XML_CONT_HAND_FAIL ERDS Evidences are generated. For the XML_CONT_HAND_FAIL ERDS Evidence the reason for failure code is one of {RE03, RE04} as specified in clause 8.3.3.5 of ETSI EN 319 522-2 [2]. For the XML_CONS_REJ ERDS Evidence, the reason for failure code is RC08 as specified in clause 8.3.3.3 of ETSI EN 319 522-2 [2].

9 Test suite for REM Baseline

9.1 Introduction

Clause 9 defines test cases for REM Baseline.

All the test cases are defined for 4-corner models based on Store&Forward to Store&Forward scenarios.

All the test cases are defined assuming only the mandatory contents for all the REM Messages.

9.2 Test cases for REM Baseline

9.2.1 Combinations of fields for the REM relay metadata header

Below follow the combinations of headers for these test cases.

Table 24: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS_REMS_RELAY_H#3	Reply-To	As specified in ETSI EN 319 532-3 [5]
	From	As specified in ETSI EN 319 532-3 [5]
	To	As recommended in ETSI EN 319 532-3 [5]
	Subject	As specified in ETSI EN 319 532-3 [5]
	Date	As recommended in ETSI EN 319 532-3 [5]
	Message-ID	As specified in ETSI EN 319 532-3 [5]
	MIME-Version	As specified in ETSI EN 319 532-3 [5]
	Content-Type	As specified in ETSI EN 319 532-3 [5]

Table 25: Combinations of new header fields defined in ETSI EN 319 532-3 [5]

Combination identifier	Field name	Value
NewFields_BS_REMS_RELAY_H#4	REM-MetadataVersion	As specified in ETSI EN 319 532-3 [5]
	REM-MessageType	As specified in ETSI EN 319 532-4 [6], clause 5.4.1
	REM-DigestAlgorithm	As specified in ETSI EN 319 532-4 [6], clause 5.4.1
	REM-DigestValue	As specified in ETSI EN 319 532-4 [6], clause 5.4.1
	REM-EventIdentifier	As specified in ETSI EN 319 532-4 [6], clause 5.4.1

9.2.2 Combinations of fields for the signed data MIME section header

Below follow the combinations of headers for these test cases.

Table 26: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS_SIGDAT_H#5	Content-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.2

9.2.3 Combinations of fields for the introduction MIME section header

Below follow the combinations of headers for these test cases.

Table 27: Combinations of new header fields defined in ETSI EN 319 532-3 [5]

Combination identifier	Field name	Value
NewFields_BS_INTR_H#1	REM-Section-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.3.1

9.2.4 Combinations of fields for the free text MIME subsection header

Below follow the combinations of headers for these test cases.

Table 28: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS_FREETXT_H#1	Content-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.3.2

9.2.5 Combinations of fields for the HTML MIME subsection header

Below follow the combinations of headers for these test cases.

Table 29: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS_HTML_H#1	Content-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.3.3

9.2.6 Combinations of fields for the original message MIME section header

Below follow the combinations of headers for these test cases.

Table 30: Combinations of new header fields defined in ETSI EN 319 532-3 [5]

Combination identifier	Field name	Value
NewFields_BS_ORMESS_H#1	REM-Section-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.4

9.2.7 Combinations of fields for the ERDS evidence MIME section header

Below follow the combinations of headers for these test cases.

Table 31: Combinations of new header fields defined in ETSI EN 319 532-3 [5]

Combination identifier	Field name	Value
NewFields_BS_EVID_H#1	REM-Section-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.6

Table 32: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS_EVID_H#1	Content-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.6

9.2.8 Combinations of fields for the REMS signature MIME section header

Below follow the combinations of headers for these test cases.

Table 33: Combinations of header fields defined in MIME and S/MIME RFCs

Combination identifier	Field name	Value
RFCFields_BS _SIG_H#1	Content-Type	As specified in ETSI EN 319 532-4 [6], clause 5.4.7
	Content-Disposition	As specified in ETSI EN 319 532-4 [6], clause 5.4.7

9.2.9 Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#3

This clause defines a number of test cases for REM Baseline built on the scenario SREMS_SF_RREMS_SF#3 in clause 5.4.2, which corresponds to the successful scenario with consignment.

NOTE 1: The REM Baseline does not include handing over operations. Therefore there can not exist test cases based on scenarios SREMS_SF_RREMS_SF#4 or SREMS_SF_RREMS_SF#5.

The first test case is for a case where the assurance level is high in both the SREM and RREM, and the mode of consignment is basic:

```

TestCase#BS_1 = SREMS_SF_RREMS_SF#3 (
  REM_dispatchInst_1_with_XML_SUB_ACC
  (REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
  high/high, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
  NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
  _SIG_H#1),

  REM_dispatchInst_2_with_XML_SUB_ACC
  (REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
  low/low, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
  NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
  _SIG_H#1),

  REMS_receipt_with_XML_SUB_ACC
  (REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
  NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
  EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

  REMS_receipt_with_XML_REL_ACC
  (REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
  NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
  EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

  REMS_receipt_with_XML_CONT_CONS
  (REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
  NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
  EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1,
  (1,0,0)
)

```

Where:

- REM_dispatchInst_1_with_XML_SUB_ACC is generated by SREMS
- REM_dispatchInst_2_with_XML_SUB_ACC is generated by RREMS
- REMS_receipt_with_XML_SUB_ACC is generated by SREMS
- REMS_receipt_with_XML_REL_ACC is generated by RREMS
- REMS_receipt_with_XML_CONT_CONS is generated by RREMS
- There is one recipient and there are not any recipient's delegate as indicated by the triplet (1,0,0)

NOTE 2: This notation fully defines the test case, because it specifies all the REM messages generated exchanged by SREMS and RREMS, the contents of the MIME headers for all the MIME sections and sub-sections in all the REM messages, the mode of consignment, and the assurance level

The second test case is for a case where the assurance level is high in both the SREM and RREM, and the mode of consignment is basic:

```

TestCase#BS_2 = SREMS_SF_RREMS_SF#3 (
REM_dispatchInst
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1,
medium/medium, basic), NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1,
NewFields_BS_ORMESS_H#1, EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS
_SIG_H#1),

REM_dispatchInst_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1,
low/low, basic), NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1,
NewFields_BS_ORMESS_H#1, EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_SUB_ACC
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),

REMS_receipt_with_XML_REL_ACC
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),

REMS_receipt_with_XML_CONT_CONS
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1
(1,0,0)
)

```

9.2.10 Test cases for REM Baseline built on scenario Scenario id: SREMS_SF_RREMS_SF#2

This clause defines a number of test cases for REM Baseline built on the scenario Scenario id: SREMS_SF_RREMS_SF#2 in clause 5.4.2, which corresponds to the simplest unsuccessful scenario where the RREMS rejects relaying of the REM Dispatch generated by the SREMS.

The first test case is for a case where the assurance level is high in both the SREMS and RREMS, the mode of consignment is basic, and the reason for the rejection by RREMS is a violation of the policy (e.g.: max message size exceeded, invalid attachment formats), whose code is RB06:

```

TestCase#BS_3 = SREMS_SF_RREMS_SF#3 (
REM_dispatchInst
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1,
high/high, basic), NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1,
NewFields_BS_ORMESS_H#1, EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),

REMS_receipt_with_XML_SUB_ACC_and_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),
(1,0,0),
RB06
)

```

Where:

- REM_dispatchInst_with_XML_SUB_ACC is generated by SREMS
- REMS_receipt_with_XML_REL_REJ is generated by RREMS
- REMS_receipt_with_XML_SUB_ACC_and_XML_REL_REJ is generated by SREMS

- There is one recipient and there is not any recipient's delegate, as indicated by the triplet (1,0,0)
- The RREMS rejects the relaying because there is a violation of the policy (as indicated by the last parameter RA05)

The second test case is identical to the first one but now the reason for the rejection by RREMS is an invalid message format (code RB02):

```

TestCase#BS_4 = SREMS_SF_RREMS_SF#3 (
REM_dispatchInst
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
high/high, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_SUB_ACC_and_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),
(1,0,0),
RB02
)

```

The third test case is identical to the first and second ones but now the reason for the rejection by RREMS is that the signature is invalid (code RB04):

```

TestCase#BS_5 = SREMS_SF_RREMS_SF#3 (
REM_dispatchInst
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
high/high, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_SUB_ACC_and_XML_REL_REJ
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),
(1,0,0),
RB04
)

```

9.2.11 Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#6

This clause defines a number of test cases for REM Baseline built on the scenario Scenario id: SREMS_SF_RREMS_SF#2 in clause 5.4.2, which corresponds to unsuccessful scenario where the REM Dispatch generated by the SREMS is accepted by the RREMS but there is a failure in the consignment.

The first test case is for a case where the assurance level is high in both the SREMS and RREMS, the mode of consignment is basic, and the reason for the failure in the consignment is that the quota of the recipient has been exceeded (code RD04):

```

TestCase#BS_6 = SREMS_SF_RREMS_SF#6(
REM_dispatchInst_1_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
high/high, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REM_dispatchInst_2_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
low/low, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,

```

```

NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_SUB_ACC
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_REL_ACC
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_CONT_CONS_FAIL
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

(1,0,0),
RD04
)

```

Where:

- REM_dispatchInst_1_with_XML_SUB_ACC is generated by SREMS
- REM_dispatchInst_2_with_XML_SUB_ACC is generated by RREMS
- REMS_receipt_with_XML_SUB_ACC is generated by SREMS
- REMS_receipt_with_XML_REL_ACC is generated by RREMS
- REMS_receipt_with_XML_CONT_FAIL is generated by RREMS
- There is one recipient and there are not any recipient's delegate as indicated by the triplet (1,0,0). Therefore only REMS_receipt_with_XML_CONT_FAIL is generated
- The reason for the consignment is that the quota of the recipient has been exceeded (code RD04)

The second test case is as the first one but now the reason for failure in the consignment is that there is some technical malfunction (code RD05):

```

TestCase#BS_7 = SREMS_SF_RREMS_SF#6(
REM_dispatchInst_1_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
high/high, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REM_dispatchInst_2_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1,
low/low, basic), NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1,
NewFields_BS _ORMESS_H#1, EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS
_SIG_H#1),

REMS_receipt_with_XML_SUB_ACC
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_REL_ACC
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

REMS_receipt_with_XML_CONT_CONS_FAIL
(REMSRelayMetadata(FCFields_BS _REMS_RELAY_H#1, NewFields_BS _REMS_RELAY_H#1, low/low, basic),
NewFields_BS _INTR_H#1, RFCFields_BS _FREETXT_H#1, RFCFields_BS _HTML_H#1, NewFields_BS _ORMESS_H#1,
EVID(RFCFields_BS _EVID_H#1, NewFields_BS _EVID_H#1), RFCFields_BS _SIG_H#1),

(1,0,0),
RD05
)

```

9.2.12 Test cases for REM Baseline built on scenario SREMS_SF_RREMS_SF#1

This clause defines a number of test cases for REM Baseline built on the scenario Scenario id: SREMS_SF_RREMS_SF#2 in clause 5.4.2, which corresponds to unsuccessful scenario where the SREMS rejects the original message sent by the sender.

The first test case is for a case where the assurance level is high in both the SREMS and RREMS, the mode of consignment is basic, and the reason for the rejection is a policy violation by the sender (e.g. max message size exceeded, invalid attachment formats, etc.), whose code is RA05:

```
TestCase#BS_8 = SREMS_SF_RREMS_SF#6(
REMS_receipt_with_XML_SUB_REJ
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),
(1,0,0),
RA05
)
```

Where:

- REMS_receipt_with_XML_SUB_REJ is generated by SREMS
- The reason for the consignment is a violation of the policy by the sender (code RA05)

The second test case is for a case where the assurance level is high in both the SREMS and RREMS, the mode of consignment is basic, and the reason for the rejection is that there is a problem with the format of the original message (code RA02):

```
TestCase#BS_9 = SREMS_SF_RREMS_SF#6(
REMS_receipt_with_XML_SUB_REJ
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),
(1,0,0),
RA02
)
```

9.2.13 Test case for REM Baseline built on scenario SREMS_SF_RREMS_SF#7

This clause defines one test case for REM Baseline built on the scenario SREMS_SF_RREMS_SF#7 in clause 5.4.2, which corresponds to unsuccessful scenario where the SREMS does not receive the ContentConsignment ERDS Evidence during the period time predefined for receiving it (code RD03).

```
TestCase#BS_10 = SREMS_SF_RREMS_SF#32 (
REM_dispatchInst_1_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1,
high/high, basic), NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1,
NewFields_BS_ORMESS_H#1, EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS
_SIG_H#1),
REM_dispatchInst_2_with_XML_SUB_ACC
(REMSRelayMetadata(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1,
low/low, basic), NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1,
NewFields_BS_ORMESS_H#1, EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS
_SIG_H#1),
REMS_receipt_with_XML_SUB_ACC
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),
```

```

REMS_receipt_with_XML_REL_ACC
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),

REMS_receipt_with_XML_CONT_CONS_FAIL
(REMSRelayMetadata(FCFields_BS_REMS_RELAY_H#1, NewFields_BS_REMS_RELAY_H#1, low/low, basic),
NewFields_BS_INTR_H#1, RFCFields_BS_FREETXT_H#1, RFCFields_BS_HTML_H#1, NewFields_BS_ORMESS_H#1,
EVID(RFCFields_BS_EVID_H#1, NewFields_BS_EVID_H#1), RFCFields_BS_SIG_H#1),

(1,0,0),

RD03
)

```

Where:

- REM_dispatchInst_1_with_XML_SUB_ACC is generated by SREMS
- REM_dispatchInst_2_with_XML_SUB_ACC is generated by RREMS
- REMS_receipt_with_XML_SUB_ACC is generated by SREMS
- REMS_receipt_with_XML_REL_ACC is generated by RREMS
- REMS_receipt_with_XML_CONT_CONS_FAIL is generated by SREMS
- The SREM has not received in time any receipt containing ContentConsiged ERDS Evidence from RREMS (code RD03).
- There is one recipient and there are not any recipient's delegate as indicated by the triplet (1,0,0)

Annex A (informative): Change History

Date	Version	Information about changes
February 2019	1.1.1	Publication
April 2023	1.1.2	Early draft - update version 1.1.1 with resolutions to part of the comments received from stakeholders on version 1.1.1
October 2023	1.1.3	Final draft for TS Approval. This version includes the implementation of resolutions to all the comments received to versions v 1.1.1 and v1.1.2. It includes two new scenarios for Store&Forward To Store&Forward. Finally, it includes a clause defining test cases for REM Baseline.
November 2023	1.1.4	Editorial changes for fixing repetition of words, left-over text, bad numbering of some tables, and misspelled words.

History

Document history		
V1.1.1	February 2019	Publication
V1.2.1	December 2023	Publication